



### Main

Range of product	Harmony XVS Application
Product or component type	Siren
Component name	XVS
Signalling type	2 tones siren
Cable end type	With cable end

### Complementary

Material	Butadiene styrene acrylic on cone Glass reinforced polyamide 6 on body
Clamping connection capacity	<= 1 x 1.5 mm <sup>2</sup>
Cable entry	1 tapped entry for cable gland (included) , Pg 7
[Ui] rated insulation voltage	250 V conforming to EN/IEC 60947-1
Current consumption	110 mA
Sound frequency	700 Hz (+/- 15 %) 800 Hz (+/- 15 %)
[Uimp] rated impulse withstand voltage	4 kV conforming to EN/IEC 60947-1
Operating position	Any position
Product weight	0.86 kg

### Environment

Noise level	106 dB
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-40...50 °C
Class of protection against electric shock	Class II conforming to EN/IEC 61140
IP degree of protection	IP40 conforming to IEC 60529
RoHS EUR conformity date	0623
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.