
XZCR1511064D1

jumper cable XZ - male straight M12 5-pin - female straight M12 5-pin - PUR 1m



| Main | |
|------------------------------------|-------------------------------|
| Accessory / separate part category | Cabling accessories |
| Accessory / separate part type | Jumper cable |
| Male connector | M12 5 pins straight, screw-on |
| Female connector | M12 5 pins straight, screw-on |

Complementary

| Cable composition | 4 x 0.34 mm ² + 1 x 0.5 mm ² | |
|--------------------------------|--|--|
| Cable length | 1 m | |
| Wire insulation material | PUR | |
| Cable outer diameter | 5.9 mm | |
| [Ue] rated operational voltage | 36 V DC 30 V AC | |
| [In] rated current | 4 A | |
| Insulation resistance | >= 1000 MOhm | |
| Resistance across terminals | <= 5000 MOhm | |
| Product weight | 0.08 kg | |

Environment

| LITVITOTITICITE | |
|---------------------------------------|--|
| IP degree of protection | IP67 |
| Ambient air temperature for operation | -590 °C (flexing) -3590 °C (static) |
| Ambient air temperature for storage | -35100 °C |

RoHS compliance

| Terro compliance | | |
|--------------------------------|-----------|--|
| RoHS EUR status | Compliant | |
| RoHS EUR conformity date(YYWW) | 0649 | |

Schneider Blectric