



Main

Enclosure type	Weatherproof enclosure
Range of product	Kaedra
Device short name	Kaedra for modular devices
Accessories included with enclosure	1 terminal block 32 holes 1 terminal block support 2 marking kits 2 wiring straps

Complementary

Enclosure mounting	Surface
Type of front cover	Reversible Transparent
Number of horizontal rows	2
Number of 18 mm modules per row	18
Total number of 18 mm modules	36
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 32 outgoers
Distribution block outgoers	16 x 10 mm ² 16 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Plastic
Width	448 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)

Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670
Fire resistance	750 °C
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Electrical shock protection class	Class II
Ambient air temperature for operation	-25...60 °C
RoHS EUR conformity date	0648
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.