




# KJD17 Series







## Panel Cutout



## Function Options



## Water Protection Options



## FEATURES:

- Heavy Duty Industrial Design
- Electromagnet Provides Automatic Safety Protection Against Power Outages and Restarts
- PVC Cap for Dust and Water Protection

## SPECIFICATIONS:

- RATING:** 16A 120VAC [cURus UL508]  
 16A 220/240VAC [cURus UL508]  
 1/2 HP 120VAC [cURus UL508]  
 2HP 220/240VAC [cURus UL508]

- TEMPERATURE:** -25°C to 55°C  
**ELECTRICAL LIFE:** 10,000 Cycles  
**CONTACT RESISTANCE:** 50mΩ Max.  
**INSULATION RESISTANCE:** 100MΩ Min. at 500VDC  
**DIELECTRIC STRENGTH:** 1,500VAC for 1 Minute  
**INGRESS PROTECTION:** IP54 with PVC Cap

## MATERIALS:

- Body:** Polyamide 6/6  
**ACTUATOR:** Polyamide 6/6  
**CONTACTS:** Silver Alloy  
**TERMINALS:** Silver Plated Brass

PUSHBUTTON



KJD17-22212-112

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Series	Actuation Guard	Function	Voltage and Frequency	Marking Style	Water Protection	Bezel Color	Actuator Color	Marking Color
KJD17	2 - Guarded	1 - Off-On 2 - Off-On w/ Remote Trip 3 - NO+NC w/ Remote Trip	1 - 120V~/50Hz 2 - 120V~/60Hz 3 - 230V~/50Hz 4 - 230V~/60Hz 5 - 240V~/50Hz 6 - 240V~/60Hz	0 - None 1 - I/O Vert. 2 - I/O Horiz. 3 - O Only	1 - None 2 - PVC Cover 3 - PVC Cover and Rubber Gasket	1 - Black 6 - Yellow	1 - Red/Green	1 - Black 2 - White

**EXAMPLE PART NUMBERS:**

KJD17-21213-112      2P1T Off-On  
 120V 60Hz., PVC Cap, I/O Vert.

KJD17-22213-112      2P1T Off-On  
 120V 60Hz., Remote Trip, PVC Cap, I/O Vert.

