



### Main

|                    |                            |
|--------------------|----------------------------|
| Range              | Thalassa PLM               |
| Enclosure type     | Multi-purpose              |
| Category           | Compact enclosure          |
| Nominal height     | 308 mm                     |
| Nominal width      | 255 mm                     |
| Nominal depth      | 160 mm                     |
| Enclosure mounting | Wall mounted               |
| Device composition | Body 1<br>Door 1<br>Lock 2 |
| Body type          | Single piece body          |
| Door type          | Plain                      |
| Lock type          | 3 mm double-bar lock       |

### Complementary

|                             |   |
|-----------------------------|---|
| Number of locks             | 2   |
| Accessibility for operation | Front   |
| Removable parts             | Door by hinges  |
| Material                    | Polyester reinforced with fibreglass                          |
| Colour                      | Grey RAL 7032   |
| Standards                   | IEC 62208<br>NEMA classification 13<br>NEMA classification 4X |
| Product certifications      | UL  |

### Environment

|                                     |                  |
|-------------------------------------|------------------|
| IP degree of protection             | IP66 IEC 60529   |
| IK degree of protection             | IK10 IEC 62262   |
| Fire resistance                     | 960 °C IEC 62208 |
| Ambient air temperature for storage | -35...90 °C      |
| RoHS EUR status                     | Compliant        |
| RoHS EUR conformity date            | 0940             |

### Not classified

|                            |                        |
|----------------------------|------------------------|
| Mounting plate description | Without mounting plate |
|----------------------------|------------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.