

### Main

Product or component type	Communication card
Range compatibility	Altivar 312
Communication port protocol	CANopen daisy chain
Electrical connection	1 connector RJ45, Modbus 1 removable screw terminal block for inputs/outputs 2 connectors RJ45, CANopen
Transmission rate	10, 20, 50, 125, 250, 500 kbps or 1 Mbps
Number of addresses	1...127

### Complementary

Input/Output number	AI2 and AI3: 2 analog input LI1...LI3: 3 logic input R2: 1 relay output
Physical interface	RS485 multidrop serial link
Transmission frame	RTU
Communication service	1 receive SDO + 1 transmit SDO CiA 402 profile Communication monitoring node guarding and heartbeat PDO 1 : cannot be configured, asynchronous PDO 6 : can be configured, asynchronous, synchronous, cyclic asynchronous
Product weight	0.2 kg

### Environment

RoHS EUR status	Compliant
RoHS EUR conformity date	0931

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.