

# LC1F115GD

contactor TeSys LC1-F - 3 poles - AC-3 - 440V  
115 A - coil 125 V DC



## Main

Range of product	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Control circuit type	DC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	115 A ( $\leq 55$ °C) AC AC-3 for power circuit 200 A ( $\leq 40$ °C) AC AC-1 for power circuit
Motor power kW	30 kW at 220...230 V AC 50/60 Hz 55 kW at 380...400 V AC 50/60 Hz 59 kW at 415 V AC 50/60 Hz 59 kW at 440 V AC 50/60 Hz 65 kW at 1000 V AC 50/60 Hz 75 kW at 500 V AC 50/60 Hz 80 kW at 660...690 V AC 50/60 Hz
[Uc] control circuit voltage	125 V DC
Connections - terminals	Connector power circuit: 1 cable 95 mm <sup>2</sup> Ring lugs power circuit: 1 cable 95 mm <sup>2</sup> Control circuit: connector 1 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end Control circuit: connector 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Control circuit: connector 2 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: connector 2 cable 1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end Power circuit: bars 2 - without cable end

## Complementary

Coil technology	Built-in bidirectional peak limiting diode suppressor
Auxiliary contacts type	Type integrated in coil (1 NO)
Auxiliary contact composition	1 NO
Control circuit voltage limits	0.15...0.2 U <sub>c</sub> at $\leq 55$ °C drop-out 0.85...1.1 U <sub>c</sub> at $\leq 55$ °C operational
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-1 for power circuit 1500 V conforming to VDE 0110 group C for power circuit
[Uimp] rated impulse withstand voltage	8 kV coil not connected to the power circuit
Mounting support	Plate Rail
Tightening torque	Power circuit: 10 N.m - on bars Power circuit: 10 N.m - on connector - cable 95 mm <sup>2</sup> Power circuit: 10 N.m - on ring lugs - cable 95 mm <sup>2</sup> Control circuit: 1.2 N.m - on connector - cable 1...2.5 mm <sup>2</sup> Control circuit: 1.2 N.m - on connector - cable 1...4 mm <sup>2</sup>
[Ue] rated operational voltage	$\leq 1000$ V AC 16 Hz 2/3...200 Hz for power circuit
[Ith] conventional free air thermal current	200 A at $\leq 40$ °C for power circuit
Irms rated making capacity	1150 A at $\leq 1000$ V AC for power circuit conforming to IEC 60497-4-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Rated breaking capacity	920 A at <= 1000 V for power circuit conforming to IEC 60497-4-1
Associated fuse rating	125 A aM at <= 440 V for power circuit 200 A gG at <= 440 V for power circuit
Average impedance	0.37 mOhm at 50 Hz - lth 200 A for power circuit
Power dissipation per pole	15 W AC-1 5 W AC-3
Inrush power in W	560 W at 20 °C
Hold-in power consumption in W	4.5 W at 20 °C
Operating time	30...40 ms on closing 30...50 ms on opening
Mechanical durability	10000000 cycles
Operating rate	2400 cyc/h at <= 55 °C
Height	163.5 mm
Width	162 mm
Depth	171 mm
Product weight	3.43 kg

## Environment

Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JEM 1038
Product certifications	BV CCC CSA DNV (Det Norske Veritas) GL GOST LROS (Lloyds register of shipping) RINA RMR0S UL
IP degree of protection	IP20 front face with cover conforming to IEC 60529 IP20 front face with cover conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-60...80 °C
Ambient air temperature for storage	-5...55 °C
Permissible ambient air temperature around the device	-40...70 °C at U <sub>c</sub>
Operating altitude	3000 m without derating in temperature
Fire resistance	850 °C conforming to IEC 60695-2-1
Shock resistance	15 gn contactor closed 9 gn contactor opened
Vibration resistance	2 gn 5...300 Hz contactor opened 6 gn 5...300 Hz contactor closed