

MITSUBISHI HVIGBT MODULES
CM1200HA-34H

HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

HIGH POWER SWITCHING USE
INSULATED TYPE

CM1200HA-34H




- Ic 1200A
- VCES 1700V
- Insulated Type
- 1-element in a pack

APPLICATION

Inverters, Converters, DC choppers, Induction heating, DC to DC converters.

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



HVIGBT MODULES (High Voltage Insulated Gate Bipolar Transistor Modules)

Mar. 2003



CM1200HA-34H

HIGH POWER SWITCHING USE
INSULATED TYPE

HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

MAXIMUM RATINGS (Tj = 25°C)

Symbol	Item	Conditions	Ratings	Unit
VCES	Collector-emitter voltage	VGE = 0V	1700	V
VGES	Gate-emitter voltage	VCE = 0V	±20	V
IC	Collector current	DC, Tc = 95°C	1200	A
ICM		Pulse (Note 1)	2400	A
IE (Note 2)	Emitter current		1200	A
IEM (Note 2)		Pulse (Note 1)	2400	A
PC (Note 3)	Maximum collector dissipation	Tc = 25°C, IGBT part	13800	W
Tj	Junction temperature	—	-40 ~ +150	°C
Tstg	Storage temperature	—	-40 ~ +125	°C
Viso	Isolation voltage	Charged part to base plate, rms, sinusoidal, AC 60Hz 1min.	4000	V
—	Mounting torque	Main terminals screw M8	6.67 ~ 13.00	N·m
		Mounting screw M6	2.84 ~ 6.00	N·m
		Auxiliary terminals screw M4	0.88 ~ 2.00	N·m
—	Mass	Typical value	1.5	kg

ELECTRICAL CHARACTERISTICS (Tj = 25°C)

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
ICES	Collector cutoff current	VCE = VCES, VGE = 0V	—	—	30	mA
VGE(th)	Gate-emitter threshold voltage	IC = 120mA, VCE = 10V	4.5	5.5	6.5	V
IGES	Gate-leakage current	VGE = VGES, VCE = 0V	—	—	0.5	µA
VCE(sat)	Collector-emitter saturation voltage	Tj = 25°C	—	2.75	3.58	V
		Tj = 125°C	—	3.30	—	
Cies	Input capacitance	VCE = 10V VGE = 0V	—	140	—	nF
Coes	Output capacitance		—	20.0	—	nF
Cres	Reverse transfer capacitance		—	7.6	—	nF
QG	Total gate charge	VCC = 850V, IC = 1200A, VGE = 15V	—	6.6	—	µC
td(on)	Turn-on delay time	VCC = 850V, IC = 1200A	—	—	1.20	µs
tr	Turn-on rise time	VGE1 = VGE2 = 15V	—	—	1.50	µs
td(off)	Turn-off delay time	RG = 1.6Ω	—	—	2.00	µs
tf	Turn-off fall time	Resistive load switching operation	—	—	0.60	µs
VEC (Note 2)	Emitter-collector voltage	IE = 1200A, VGE = 0V	—	2.40	3.12	V
trr (Note 2)	Reverse recovery time	IE = 1200A	—	—	2.00	µs
Qrr (Note 3)	Reverse recovery charge	die / dt = -2400A / µs	—	200	—	µC
Rth(j-c)Q	Thermal resistance	Junction to case, IGBT part	—	—	0.009	K/W
Rth(j-c)R		Junction to case, FWDI part	—	—	0.028	K/W
Rth(c-f)	Contact thermal resistance	Case to fin, conductive grease applied	—	0.008	—	K/W

- Note 1. Pulse width and repetition rate should be such that the device junction temp. (Tj) does not exceed Tjmax rating.
 2. IE, VEC, trr, Qrr & die/dt represent characteristics of the anti-parallel, emitter to collector free-wheel diode.
 3. Junction temperature (Tj) should not increase beyond 150°C.
 4. Pulse width and repetition rate should be such as to cause negligible temperature rise.




CM1200HA-34H

HIGH POWER SWITCHING USE
INSULATED TYPE


HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

PERFORMANCE CURVES


OUTPUT CHARACTERISTICS (TYPICAL)




TRANSFER CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)



CAPACITANCE CHARACTERISTICS (TYPICAL)




CM1200HA-34H


HIGH POWER SWITCHING USE
INSULATED TYPE

HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules


HALF-BRIDGE SWITCHING TIME CHARACTERISTICS (TYPICAL)




REVERSE RECOVERY CHARACTERISTICS OF FREE-WHEEL DIODE (TYPICAL)




HALF-BRIDGE SWITCHING ENERGY CHARACTERISTICS (TYPICAL)



HALF-BRIDGE SWITCHING ENERGY CHARACTERISTICS (TYPICAL)



GATE CHARGE CHARACTERISTICS (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS

