

August 2009

# FYP2010DN Schottky Barrier Rectifier

## **Features**

- · Low forward voltage drop
- · High frequency properties and switching speed
- Guard ring for over-voltage protection



## **Absolute Maximum Ratings** T<sub>A</sub>=25°C unless otherwise noted

Symbol	Parameter	Value	Units
V <sub>RRM</sub>	Maximum Repetitive Reverse Voltage	100	V
V <sub>R</sub>	Maximum DC Reverse Voltage	100	V
I <sub>F(AV)</sub>	Average Rectified Forward Current @ T <sub>C</sub> = 120°C	20	А
I <sub>FSM</sub>	Non-repetitive Peak Surge Current (per diode) 60Hz Single Half-Sine Wave	150	Α
T <sub>J,</sub> T <sub>STG</sub>	Operating Junction and Storage Temperature	-65 to +150	°C

## **Thermal Characteristics**

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Maximum Thermal Resistance, Junction to Case (per diode)	1.7	°C/W

## Electrical Characteristics (per diode)

Symbol	Parameter		Value	Units
V <sub>FM</sub> *	Maximum Instantaneous Forward Voltage $I_F = 10A$ $I_F = 10A$ $I_F = 20A$ $I_F = 20A$	$T_{C} = 25 ^{\circ}\text{C}$ $T_{C} = 125 ^{\circ}\text{C}$ $T_{C} = 25 ^{\circ}\text{C}$ $T_{C} = 125 ^{\circ}\text{C}$	0.77 0.65 - 0.75	V
I <sub>RM</sub> *	Maximum Instantaneous Reverse Current @ rated V <sub>R</sub>	$T_C = 25  ^{\circ}C$ $T_C = 125  ^{\circ}C$	0.1 20	mA

<sup>\*</sup> Pulse Test: Pulse Width=300µs, Duty Cycle=2%

© 2009 Fairchild Semiconductor Corporation

FYP2010DN Rev. B1

www.fairchildsemi.com

## **Typical Performance Characteristics**




Figure 1. Typical Forward Voltage Characteristics (per diode)




Figure 2. Typical Reverse Current vs. Reverse Voltage (per diode)




Figure 3. Typical Junction Capacitance (per diode)




Figure 4. Thermal Impedance Characteristics (per diode)




Figure 5. Forward Current Derating Curve




Figure 6. Non-Repetive Surge Current (per diode)

# **Physical Dimensions TO-220** Ø<sub>3.50</sub>△ ⊕ 0.36 **M** B A**M** 10.67 9.65 8.89 6.86 3.43 2.54 16.51 14.22 △9.40 8.38 6.35 MAX (1.91)1.02 0.38 2.92 2.03 → 0.36 M B AM 2.54 NOTES: UNLESS OTHERWISE SPECIFIED A) REFERENCE JEDEC, TO-220, ISSUE K, VARIATION AB, DATED APRIL, 2002. B) ALL DIMENSIONS ARE IN MILLIMETERS. C) DIMENSIONING AND TOLERANCING PER 5.08 C) DIMENSIONING AND TOLERANGING FER ANSI Y14.5 - 1973 D) LOCATION OF THE PIN HOLE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE) ∕E\DOES NOT COMPLY JEDEC STANDARD VALUE. "A1" DIMENSIONS REPRESENT LIKE BELOW: SINGLE GAUGE = 0.51 - 0.61 DUAL GAUGE = 1.14 - 1.40 G) DRAWING FILE NAME: TO220B03REV6



#### **TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ FPS™ Auto-SPM™ F-PESTM FRFET® Build it Now™

Global Power Resource<sup>SM</sup> CorePLUS™

CorePOWER™ Green FPS™  $CROSSVOLT^{\text{\tiny IM}}$ Green FPS™ e-Series™ CTL™ Gmax™

Current Transfer Logic™ GTO™ EcoSPARK® IntelliMAX™ EfficentMax™ ISOPLANAR™ EZSWITCH™\* MegaBuck™ MICROCOUPLER™

MicroFET™ MicroPak™ MillerDrive™ Fairchild® MotionMax™ Fairchild Semiconductor® Motion-SPM™ OPTOLOGIC®

FACT Quiet Series™ FACT® FAST® FastvCore™

FETBench™ PDP SPMTM FlashWriter®\* Power-SPM™ PowerTrench® PowerXS™

Programmable Active Droop™

OFĔT QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™ SmartMax™

SMART START™ SPM<sup>®</sup> STEALTH™ SuperFET™ SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS™ . SyncFET™ Sync-Lock™ SYSTEM ® GENERAL

The Power Franchise®

puwer TinyBoost™ TinyBuck™ TinyCalc™ TinyLogic<sup>®</sup> TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TriFault Detect™ TRUECURRENT™\*

μSerDes™ UHC Ultra FRFET™ UniFFT™ VCX™

VisualMax™ XSTM

OPTOPLANAR®

#### DISCL AIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### PRODUCT STATUS DEFINITIONS

#### **Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete Not In Production		Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. 141

<sup>\*</sup> Trademarks of System General Corporation, used under license by Fairchild Semiconductor.