

SLE 66CLX1280PE (M/S)

**8/16-Bit High Security Dual Interface Controller
For Contact based and Contactless Applications
ISO/IEC 7816 and 14443 Type B & A Compliant Interfaces
Contactless interface acc. ISO/IEC 18092 passive mode
(SONY FeliCa® communication interface)**

with Linear Addressing Instruction Set For Large Memories
in 0.22 μm CMOS Technology 240-Kbyte User ROM, 7100-byte RAM,
128-Kbyte EEPROM

1100-Bit Advanced Crypto Engine

supporting RSA and Elliptic Curve GF(p)

certified RSA 2048-bit library available

112-Bit Dual Key DES Accelerator
supporting DES, 3DES Algorithms

Short Product Overview

May 2011

Chip Card & Security



SLE 66CLX1280PE (M/S) Short Product Overview		Ref.: Chip_Card_Product_Overview_11/09
Revision History: Current Version 05.11		
Previous Releases: 05.10		
Page		

Important: Further information is confidential and on request. Please contact:
Infineon Technologies AG in Munich, Germany,
Chip Card & Security
E-Mail: security.chipcard.ics@infineon.com

Edition 2010

**Published by Infineon Technologies AG,
Chip Card & Security
81726 Munich, Germany
© Infineon Technologies AG 2011
All Rights Reserved.**

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Product name	SLE 66CLX1280PE (M/S)
Product description	Dual-interface and contactless security cryptocontroller
Interfaces	ISO 7816, ISO 14443, ISO 18092 passive mode, Mifare compatible interface
User-ROM	240kByte (236kByte)
Flash	–
EEPROM	128kByte (128kByte + 1kByte for M)
RAM	6kByte XRAM, 700Byte Crypto, 256Byte IRAM
CPU	8-bit/16-bit
Symmetrical Cryptography	3DES
Asymmetrical Cryptography	RSA up to 2048-bit, ECC up to 521-bit
Ambient temperature	-25 to +70°C
Delivery forms	Module M8.4, contactless module MCC8, die, bumped wafer
Typical applications	Payment, EMV DDA, ePurse, Loyalty, Access Control, Digital Signature, ePassport, Open Platform, Dual SIM
Certifications	CC EAL5+ high, EMVCo

For further information on technology, delivery forms and conditions please contact your nearest Infineon Technologies sales representative (www.infineon.com).

www.infineon.com

Published by Infineon Technologies AG