

SLE 77CLFX2400P (M7794)

16-bit Security Controller with "SOLID FLASH™",
optimized for Contactless and Dual-Interface
Payment Applications in 90 nm CMOS Technology

240 Kbytes SOLID FLASH™
6 Kbytes RAM
27 pF Chip Input Capacitance

ISO/IEC 7816 Contactbased and
ISO/IEC 14443 Type B Compliant Contactless Interfaces
Contactless Interface acc. ISO/IEC 18092 (NFC Passive Mode)
Optionally ISO/IEC 14443 Type A Contactless Interfaces

Crypto@2304T Engine
with Register Lengths of up to 2304 bits,
certified RSA and ECC Libraries

Symmetric Crypto Processor (SCP)

Short Product Overview

Revision November 2011



Chip Card & Security

SLE 77CLFX2400P Short Product Overview	Ref.: SPO_SLE 77CLFX2400P 05.11
Revision History: Current Version 11.11	
Previous Releases: 05.11	
Page	

Edition 2011-10-01

**Published by
Infineon Technologies AG
81726 Munich, Germany**

**© 2011 Infineon Technologies AG
All Rights Reserved.**

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Product name	SLE 77CLFX2400P
Featured icon	Solid Flash
Product description	Dual-interface and contactless security cryptocontroller
Interfaces	ISO 7816, ISO 14443 A/B, ISO 18092 passive mode, prepared for sub ID1 dedicated products
User-ROM	–
Flash	240kByte
EEPROM	–
RAM	6kByte
CPU	16-bit
Crypto coprocessor symmetrical	DES, 3DES, AES up to 256-bit
Crypto coprocessor asymmetrical	RSA up to 4096-bit, ECC up to 521-bit
Ambient temperature	-25 to +85°C
Delivery forms	contactless module, die, dual interface module
Typical applications	Basic ID, Payment, EMV DDA, ePurse, Loyalty, Access Control, Transport, Open Platform
Certifications	CC EAL4+ targeted, EMVCo targeted

If you don't find your required derivative, please contact us for further information (www.infineon.com).

Infineon Technologies – innovative semiconductor solutions for energy efficiency, mobility and security.



www.infineon.com

Published by Infineon Technologies AG