

Series PVT412 & PbF

Microelectronic Power IC

HEXFET® Power MOSFET Photovoltaic Relay

Single Pole, Normally Open,

0-400V, 140mA AC/DC

General Description

The PVT412 Series Photovoltaic Relay is a single-pole, normally open solid-state relay that can replace electromechanical relays in many applications. It utilizes International Rectifier's proprietary HEXFET power MOSFET as the output switch, driven by an integrated circuit photovoltaic generator of novel construction. The output switch is controlled by radiation from a GaAlAs light emitting diode (LED) which is optically isolated from the photovoltaic generator.

These SSRs are specifically designed for worldwide telecom applications. PVT412L employs an active current-limiting circuitry enabling it to pass FCC Part 68 and other regulatory agency current surge requirements when overvoltage protection is provided. PVT412 does not employ the current-limiting circuitry and offers lower on-state resistance.


Series PVT412 Relays are packaged in a 6-lead molded DIP package with either thru-hole or surface mount (gull-wing) terminals. It is available in standard plastic shipping tubes or on tape-and-reel. Please refer to part identification information opposite.

Applications

- On/Off Hook switch
- Dial-Out relay
- Ring relay
- General switching

Features

- HEXFET Power MOSFET output
- Bounce-free operation
- 4,000 V_{RMS} I/O isolation
- Load current limiting
- Linear AC/DC operation
- Solid-State Reliability
- UL recognized and BABT certified
- ESD Tolerance:
 - 4000V Human Body Model
 - 500V Machine Model



Part Identification

| | |
|------------------|--|
| PVT412L & PbF | current limit, thru-hole |
| PVT412LS & PbF | current limit, surface-mount |
| PVT412LS-T & PbF | current limit, surface-mount, Tape and Reel |
| PVT412 & PbF | no current limit, thru-hole |
| PVT412S & PbF | no current limit, surface-mount |
| PVT412S-T & PbF | no current limit, surface-mount, Tape and Reel |

(HEXFET is the registered trademark for International Rectifier Power MOSFETs)

Electrical Specifications ($-40^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$ unless otherwise specified)

| INPUT CHARACTERISTICS | Part Numbers | | Units |
|--|--------------|--------|-------|
| | PVT412L | PVT412 | |
| Minimum Control Current (see figures 1 and 2) | 3.0 | | mA |
| Maximum Control Current for Off-State Resistance | 0.4 | | mA |
| Control Current Range (Caution: current limit input LED, see figure 6) | 3.0 to 25 | | mA |
| Maximum Reverse Voltage | 6.0 | | V |

| OUTPUT CHARACTERISTICS | PVT412L | | PVT412 | Units |
|---|----------------|----------|--------|-------------------------------------|
| | | | | |
| Operating Voltage Range | 0 to ± 400 | | | V(DC or AC peak) |
| Maximum Load Current @ $T_A=+40^{\circ}\text{C}$ 5mA Control (see figures 1 and 2) | | | | mA (AC or DC) mA (DC) mA (DC) |
| A Connection | 120 | 140 | | |
| B Connection | 130 | 150 | | |
| C Connection | 200 | 210 | | |
| Maximum On-State Resistance @ $T_A=+25^{\circ}\text{C}$ For 50mA Pulsed Load, 5mA Control (see figure 4) | | | | Ω Ω Ω |
| A Connection | 35 | 27 | | |
| B Connection | 18 | 14 | | |
| C Connection | 9 | 7 | | |
| Maximum Off-State Leakage @ $T_A=+25^{\circ}\text{C}$, $\pm 400\text{V}$ (see figure 5) | 1.0 | | | μA |
| Current Limit @ $T_A=+25^{\circ}\text{C}$, For 5mA Control Current: | | | | mA mA |
| Connection: | A | C | | |
| Minimum | 130 | 260 | n/a | |
| Maximum | 220 | 440 | n/a | |
| Complies with FCC Part 68 Surge Requirements* | yes | | yes | |
| Maximum Turn-On Time @ $T_A=+25^{\circ}\text{C}$ (see figure 7) For 50mA, 100 V _{DC} load, 5mA Control | 2.0 | | | ms |
| Maximum Turn-Off Time @ $T_A=+25^{\circ}\text{C}$ (see figure 7) For 50mA, 100 V _{DC} load, 5mA Control | 0.5 | | | ms |
| Maximum Thermal Offset Voltage @ 5mA Control | 0.5 | | | μV |
| Maximum Output Capacitance @ 50V _{DC} | 12 | | | pF |

| GENERAL CHARACTERISTICS | ALL MODELS | | Units |
|---|------------|-------------|--------------------|
| Minimum Dielectric Strength, Input-Output | 4000 | | V _{RMS} |
| Minimum Insulation Resistance, Input-Output @ $T_A=+25^{\circ}\text{C}$, 50%RH, 100V _{DC} | 10^{12} | | Ω |
| Maximum Capacitance, Input-Output | 1.0 | | pF |
| Maximum Pin Soldering Temperature (10 seconds maximum) | +260 | | $^{\circ}\text{C}$ |
| Ambient Temperature Range: | Operating | -40 to +85 | |
| | Storage | -40 to +100 | |

International Rectifier does not recommend the use of this product in aerospace, avionics, military or life support applications. Users of this International Rectifier product in such applications assume all risks of such use and indemnify International Rectifier against all damages resulting from such use.

Connection Diagrams





Figure 1. Current Derating Curves*




Figure 2. Current Derating Curves*

* Derating of 'B' and 'C' connection at +85 C will be 70% of that specified at +40 C and is linear from +40 C to +85 C.




Figure 3. Linearity Characteristics




Figure 4. Typical Normalized On-Resistance




Figure 5. Typical Normalized Off-State Leakage




Figure 6. Input Characteristics (Current Controlled)




Figure 7. Typical Delay Times




Figure 8. Delay Time Definitions




Figure 9. Typical Output Capacitance

Case Outlines

