


## 1-A Dual-HBD (Dual-Half-Bridge Driver)

TLE 4207

### Overview

### Features

- Delivers up to 0.8 A continuous
- Optimized for DC motor management applications
- Very low current consumption in stand-by (Inhibit) mode
- Low saturation voltage; typ.1.2 V total @ 25 °C; 0.4 A
- Output protected against short circuit
- Error flag diagnosis
- Overvoltage lockout and diagnosis
- Undervoltage lockout
- CMOS/TTL compatible inputs with hysteresis
- No crossover current
- Internal clamp diodes
- Overtemperature protection with hysteresis and diagnosis
- Enhanced power P-DSO-Package



Type	Ordering Code	Package
TLE 4207 G	Q67006-A9275	P-DSO-14-8

### Description


The TLE 4207 is a fully protected **Dual-Half-Bridge-Driver** designed specially for automotive and industrial motion control applications.

The part is built using the Siemens bipolar high voltage power technology DOPL.

The actuator (DC motor) can be connected direct between the halfbridges. Operation modes forward (cw), reverse (ccw), brake and high impedance are invoked from a

standard interface. The standard enhanced power P-DSO-14 package meets the application requirements and saves PCB-board space and costs.

Furthermore the built in features like diagnosis, over- and undervoltage-lockout, short-circuit-protection, over-temperature-protection and the very low quiescent current in stand-by mode will open a wide range of automotive and industrial applications.




**Figure 1 Pin Configuration (top view)**

#### Pin Definitions and Functions

Pin No. P-DSO-14-8	Symbol	Function
1	$V_S$	<b>Power supply voltage;</b> positive reference potential for blocking capacitor
2	OUT2	<b>Power-output 2;</b> full short circuit protected; with integrated clamp diodes
3, 4, 5, 10, 11, 12	GND	<b>Ground;</b> <b>negative</b> reference potential for blocking capacitor
6	IN2	<b>Input channel 2;</b> controls OUT2 (not inverted)
7	INH	<b>Inhibit input;</b> low = IC in stand-by
8	EF	<b>Error Flag output;</b> open collector; low = error
9	IN1	<b>Input channel 1;</b> controls OUT1 (not inverted)

## Pin Definitions and Functions

Pin No. P-DSO-14-8	Symbol	Function
13	OUT1	<b>Power output 1; full short circuit protected; with integrated clamp diodes</b>
14	N.C.	<b>Not connected</b>



**Figure 2 Block Diagram**

### Functional Truth Table

<b>INH</b>	<b>IN1</b>	<b>IN2</b>	<b>OUT1</b>	<b>OUT2</b>	<b>Mode</b>
0	X	X	Z	Z	Stand-By
1	0	0	L	L	Brake LL
1	0	1	L	H	CW
1	1	0	H	L	CCW
1	1	1	H	H	Brake HH

IN: 0 = Logic LOW  
 1 = Logic HIGH  
 X = don't care

OUT: Z = Output in tristate condition  
 L = Output in sink condition  
 H = Output in source condition

### Diagnosis

<b>EF</b>	<b>Error</b>
1	no error
0	over temperature
0	over voltage

## Electrical Characteristics

### Absolute Maximum Ratings

Parameter	Symbol	Limit Values		Unit	Remarks
		min.	max.		

### Voltages

Supply voltage	$V_S$	- 0.3	45	V	-
Supply voltage	$V_S$	- 1	-	V	$t < 0.5 \text{ s}; I_S > - 2 \text{ A}$
Logic input voltages (IN1; IN2; INH)	$V_I$	- 5	20	V	$0 \text{ V} < V_S < 45 \text{ V}$
Logic output voltage (EF)	$V_{EF}$	- 0.3	20	V	$0 \text{ V} < V_S < 45 \text{ V}$

### Currents

Output current (cont.)	$I_{OUT1-2}$	-	-	A	internally limited
Output current (peak)	$I_{OUT1-2}$	-	-	A	internally limited
Output current (diode)	$I_{OUT1-2}$	- 1	1	A	-
Output current (EF)	$I_{OUT1-2}$	- 2	5	mA	-

### Temperatures

Junction temperature	$T_j$	- 40	150	°C	-
Storage temperature	$T_{stg}$	- 50	150	°C	-

### Thermal Resistances

Junction pin	$R_{thj-pin}$	-	25	K/W	measured to pin 5
Junction ambient	$R_{thjA}$	-	65	K/W	-

*Note: Maximum ratings are absolute ratings; exceeding any one of these values may cause irreversible damage to the integrated circuit.*

### Operating Range

Parameter	Symbol	Limit Values		Unit	Remarks
		min.	max.		
Supply voltage	$V_S$	$V_{UV\ OFF}$	18	V	After $V_S$ rising above $V_{UV\ ON}$
Supply voltage increasing	$V_S$	- 0.3	$V_{UV\ ON}$	V	Outputs in tristate
Supply voltage decreasing	$V_S$	- 0.3	$V_{UV\ OFF}$	V	Outputs in tristate
Logic input voltage (IN1; IN2; INH)	$V_I$	- 2	18	V	-
Junction temperature	$T_j$	- 40	150	°C	-

*Note: In the operating range the functions given in the circuit description are fulfilled.*

## Electrical Characteristics

$8 \text{ V} < V_S < 18 \text{ V}$ ; INH = High;  $I_{\text{OUT1-2}} = 0 \text{ A}$ ;  $-40^\circ\text{C} < T_j < 150^\circ\text{C}$ ;  
unless otherwise specified

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		

## Current Consumption

Quiescent current	$I_S$	—	20	50	$\mu\text{A}$	$\text{INH} = \text{LOW}$
Quiescent current	$I_S$	—	20	30	$\mu\text{A}$	$\text{INH} = \text{LOW};$ $V_S = 13.2 \text{ V}$ ; $T_j = 25^\circ\text{C}$
Supply current	$I_S$	—	10	20	$\text{mA}$	—
Supply current	$I_S$	—	—	30	$\text{mA}$	$I_{\text{OUT1}} = 0.4 \text{ A}$ $I_{\text{OUT2}} = -0.4 \text{ A}$
Supply current	$I_S$	—	—	50	$\text{mA}$	$I_{\text{OUT1}} = 0.8 \text{ A}$ $I_{\text{OUT2}} = -0.8 \text{ A}$

## Over- and Under Voltage Lockout

UV Switch ON voltage	$V_{\text{UV ON}}$	—	6.5	7.5	$\text{V}$	$V_S$ increasing
UV Switch OFF voltage	$V_{\text{UV OFF}}$	5.0	6	—	$\text{V}$	$V_S$ decreasing
UV ON/OFF hysteresis	$V_{\text{UV HY}}$	—	0.5	—	$\text{V}$	$V_{\text{UV ON}} - V_{\text{UV OFF}}$
OV Switch OFF voltage	$V_{\text{OV OFF}}$	—	20	24	$\text{V}$	$V_S$ increasing
OV Switch ON voltage	$V_{\text{OV ON}}$	18.0	19.5	—	$\text{V}$	$V_S$ decreasing
OV ON/OFF hysteresis	$V_{\text{OV HY}}$	—	0.5	—	$\text{V}$	$V_{\text{OV OFF}} - V_{\text{OV ON}}$

### Electrical Characteristics (cont'd)

$8 \text{ V} < V_S < 18 \text{ V}$ ; INH = High;  $I_{\text{OUT1-2}} = 0 \text{ A}$ ;  $-40^\circ\text{C} < T_j < 150^\circ\text{C}$ ;  
unless otherwise specified

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		

### Outputs OUT1-2

#### Saturation Voltages

Source (upper) $I_{\text{OUT}} = -0.2 \text{ A}$	$V_{\text{SAT U}}$	—	0.85	1.15	V	$T_j = 25^\circ\text{C}$
Source (upper) $I_{\text{OUT}} = -0.4 \text{ A}$	$V_{\text{SAT U}}$	—	0.90	1.20	V	$T_j = 25^\circ\text{C}$
Sink (upper) $I_{\text{OUT}} = -0.8 \text{ A}$	$V_{\text{SAT U}}$	—	1.10	1.50	V	$T_j = 25^\circ\text{C}$
Sink (lower) $I_{\text{OUT}} = 0.2 \text{ A}$	$V_{\text{SAT L}}$	—	0.15	0.23	V	$T_j = 25^\circ\text{C}$
Sink (lower) $I_{\text{OUT}} = 0.4 \text{ A}$	$V_{\text{SAT L}}$	—	0.25	0.40	V	$T_j = 25^\circ\text{C}$
Sink (lower) $I_{\text{OUT}} = 0.8 \text{ A}$	$V_{\text{SAT L}}$	—	0.45	0.75	V	$T_j = 25^\circ\text{C}$

Total Drop $I_{\text{OUT}} = 0.2 \text{ A}$	$V_{\text{SAT}}$	—	1	1.4	V	$V_{\text{SAT}} = V_{\text{SAT U}} + V_{\text{SAT L}}$
Total Drop $I_{\text{OUT}} = 0.4 \text{ A}$	$V_{\text{SAT}}$	—	1.2	1.7	V	$V_{\text{SAT}} = V_{\text{SAT U}} + V_{\text{SAT L}}$
Total Drop $I_{\text{OUT}} = 0.8 \text{ A}$	$V_{\text{SAT}}$	—	1.6	2.5	V	$V_{\text{SAT}} = V_{\text{SAT U}} + V_{\text{SAT L}}$

#### Clamp Diodes

Forward voltage; upper	$V_{\text{FU}}$	—	1	1.5	V	$I_F = 0.4 \text{ A}$
Upper leakage current	$I_{\text{LKU}}$	—	—	5	mA	$I_F = 0.4 \text{ A}^1)$
Forward voltage; lower	$V_{\text{FL}}$	—	0.9	1.4	V	$I_F = 0.4 \text{ A}$

Notes see page 10.

### Electrical Characteristics (cont'd)

$8 \text{ V} < V_S < 18 \text{ V}$ ; INH = High;  $I_{\text{OUT1-2}} = 0 \text{ A}$ ;  $-40^\circ\text{C} < T_j < 150^\circ\text{C}$ ;  
unless otherwise specified

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		

### Input-Interface

#### Logic Inputs IN1; IN2

H-input voltage	$V_{IH}$	—	2	3	V	—
L-input voltage	$V_{IL}$	1	1.5	—	V	—
Hysteresis of input voltage	$V_{IHY}$	—	0.5	—	V	—
H-input current	$I_{IH}$	— 2	—	10	$\mu\text{A}$	$V_I = 5 \text{ V}$
L-input current	$I_{IL}$	— 100	— 20	— 5	$\mu\text{A}$	$V_I = 0 \text{ V}$

#### Logic Input INH

H-input voltage	$V_{IH}$	—	2.7	3.5	V	—
L-input voltage	$V_{IL}$	1	2	—	V	—
Hysteresis of input voltage	$V_{IHY}$	—	0.7	—	V	—
H-input current	$I_{IH}$	—	100	250	$\mu\text{A}$	$V_{INH} = 5 \text{ V}$
L-input current	$I_{IL}$	— 10	—	10	$\mu\text{A}$	$V_{INH} = 0 \text{ V}$

#### Error-Flag EF

L-output voltage level	$V_{EFL}$	—	0.2	0.4	V	$I_{EF} = 2 \text{ mA}$
Leakage current	$I_{EFLK}$	—	—	10	$\mu\text{A}$	$0 \text{ V} < V_{EF} < 7 \text{ V}$

### **Electrical Characteristics (cont'd)**

$8 \text{ V} < V_S < 18 \text{ V}$ ; INH = High;  $I_{\text{OUT1-2}} = 0 \text{ A}$ ;  $-40^\circ\text{C} < T_j < 150^\circ\text{C}$ ;  
unless otherwise specified


<b>Parameter</b>	<b>Symbol</b>	<b>Limit Values</b>			<b>Unit</b>	<b>Test Condition</b>
		<b>min.</b>	<b>typ.</b>	<b>max.</b>		

### **Thermal Shutdown**

Thermal shutdown junction temperature	$T_{jSD}$	150	175	200	°C	–
Thermal switch-on junction temperature	$T_{jSO}$	120	–	170	°C	–
Temperature hysteresis	$\Delta T$	–	30	–	K	–

<sup>1)</sup> Guaranteed by design.


*Note: The listed characteristics are ensured over the operating range of the integrated circuit. Typical characteristics specify mean values expected over the production spread. If not otherwise specified, typical characteristics apply at  $T_A = 25^\circ\text{C}$  and the given supply voltage.*




### **Figure 3 Application Circuit**

## Diagrams


**Quiescent current  $I_S$  over Temperature**




**Saturation Voltage of Source  $V_{SATU}$  over Temperature**



**Saturation Voltage of Sink  $V_{SATL}$  over Temperature**




**Total Drop at outputs  $V_{SAT}$  over Temperature**



## Package Outlines

### P-DSO-14-8

(Plastic Dual Small Outline Package)



1) Does not include plastic or metal protrusion of 0.15 max. per side

### orts of Packing

ackage outlines for tubes, trays etc. are contained in our  
ata Book "Package Information".

SMD = Surface Mounted Device

Dimensions in mm