

FEATURES

+1.8 V to +5.5 V Single Supply
4 Ω (Max) On Resistance
0.75 Ω (Typ) On-Resistance Flatness
-3 dB Bandwidth >200 MHz
Rail-to-Rail Operation
6-Lead SOT-23 Package, 8-Lead μ SOIC Package
Fast Switching Times
 t_{ON} 20 ns
 t_{OFF} 6 ns
Typical Power Consumption (<0.01 μ W)
TTL/CMOS Compatible

APPLICATIONS

Battery Powered Systems
Communication Systems
Sample Hold Systems
Audio Signal Routing
Video Switching
Mechanical Reed Relay Replacement

GENERAL DESCRIPTION

The ADG719 is a monolithic CMOS SPDT switch. This switch is designed on a submicron process that provides low power dissipation yet gives high switching speed, low on resistance and low leakage currents.


The ADG719 can operate from a single supply range of +1.8 V to +5.5 V, making it ideal for use in battery-powered instruments and with the new generation of DACs and ADCs from Analog Devices.

Each switch of the ADG719 conducts equally well in both directions when on. The ADG719 exhibits break-before-make switching action.

Because of the advanced submicron process, -3 dB bandwidths of greater than 200 MHz can be achieved.

The ADG719 is available in a 6-lead SOT-23 package and an 8-lead μ SOIC package.

FUNCTIONAL BLOCK DIAGRAM



SWITCHES SHOWN FOR A LOGIC "1" INPUT

PRODUCT HIGHLIGHTS

1. +1.8 V to +5.5 V Single Supply Operation. The ADG719 offers high performance, including low on resistance and fast switching times and is fully specified and guaranteed with +3 V and +5 V supply rails.
2. Very Low R_{ON} (4 Ω max at 5 V, 10 Ω max at 3 V). At 1.8 V operation, R_{ON} is typically 40 Ω over the temperature range.
3. On-Resistance Flatness ($R_{FLAT(ON)}$) (0.75 Ω typ).
4. -3 dB Bandwidth >200 MHz.
5. Low Power Dissipation. CMOS construction ensures low power dissipation.
6. Fast t_{ON}/t_{OFF} .
7. Tiny 6-lead SOT-23 and 8-lead μ SOIC packages.

REV. A

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781/329-4700 World Wide Web Site: <http://www.analog.com>
Fax: 781/326-8703 © Analog Devices, Inc., 1998

ADG719—SPECIFICATIONS¹ ($V_{DD} = +5\text{ V} \pm 10\%$, $GND = 0\text{ V}$. All specifications -40°C to $+85^{\circ}\text{C}$, unless otherwise noted.)

Parameter	B Version		Units	Test Conditions/Comments
	+25°C	−40°C to +85°C		
ANALOG SWITCH				
Analog Signal Range	4	0 V to V _{DD}	V	V _S = 0 V to V _{DD} , I _S = −10 mA Test Circuit 1
On Resistance (R _{ON})		5	Ω max	
On Resistance Match Between Channels (ΔR _{ON})		0.1	Ω typ	V _S = 0 V to V _{DD} , I _S = −10 mA
On-Resistance Flatness (R _{FLAT(ON)})	0.75	0.4	Ω max	V _S = 0 V to V _{DD} , I _S = −10 mA
		1.2	Ω typ Ω max	
LEAKAGE CURRENTS				
Source OFF Leakage I _S (OFF)	±0.01	±0.35	nA typ	V _{DD} = +5.5 V
	±0.25		nA max	V _S = 4.5 V/1 V, V _D = 1 V/4.5 V
Channel ON Leakage I _D , I _S (ON)	±0.01	±0.35	nA typ	Test Circuit 2
	±0.25		nA max	V _S = V _D = 1 V, or V _S = V _D = 4.5 V Test Circuit 3
DIGITAL INPUTS				
Input High Voltage, V _{INH}		2.4	V min	V _{IN} = V _{INL} or V _{INH}
Input Low Voltage, V _{INL}		0.8	V max	
Input Current	0.005		μA typ	
I _{INL} or I _{INH}				
DYNAMIC CHARACTERISTICS ²				
t _{ON}	14	20	ns typ	R _L = 300 Ω, C _L = 35 pF V _S = 3 V, Test Circuit 4
t _{OFF}	3		ns max	
		6	ns typ	R _L = 300 Ω, C _L = 35 pF
Break-Before-Make Time Delay, t _D	8	1	ns max	V _S = 3 V, Test Circuit 4
Off Isolation	−67		ns min	R _L = 300 Ω, C _L = 35 pF,
	−87		dB typ	V _{S1} = V _{S2} = 3 V, Test Circuit 5
Channel-to-Channel Crosstalk	−62		dB typ	R _L = 50 Ω, C _L = 5 pF, f = 10 MHz
	−82		dB typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz, Test Circuit 6
Bandwidth −3 dB	200		MHz typ	R _L = 50 Ω, C _L = 5 pF, f = 10 MHz
C _S (OFF)	7		pF typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz, Test Circuit 7
C _D , C _S (ON)	27		pF typ	R _L = 50 Ω, C _L = 5 pF, Test Circuit 8
POWER REQUIREMENTS				
I _{DD}	0.001	1.0	μA typ	V _{DD} = +5.5 V
			μA max	Digital Inputs = 0 V or 5 V

NOTES

¹Temperature ranges are as follows: B Version, -40°C to $+85^{\circ}\text{C}$.

²Guaranteed by design, not subject to production test.

Specifications subject to change without notice.

SPECIFICATIONS¹ ($V_{DD} = +3\text{ V} \pm 10\%$, $GND = 0\text{ V}$. All specifications -40°C to $+85^{\circ}\text{C}$, unless otherwise noted.)

Parameter	B Version		Units	Test Conditions/Comments
	+25°C	−40°C to +85°C		
ANALOG SWITCH				
Analog Signal Range	6	0 V to V _{DD}	V	V _S = 0 V to V _{DD} , I _S = −10 mA, Test Circuit 1
On Resistance (R _{ON})		7	Ω typ	
		10	Ω max	
On Resistance Match Between Channels (ΔR _{ON})		0.1	Ω typ	V _S = 0 V to V _{DD} , I _S = −10 mA
		0.4	Ω max	
On-Resistance Flatness (R _{FLAT(ON)})		2.5	Ω typ	V _S = 0 V to V _{DD} , I _S = −10 mA
LEAKAGE CURRENTS				
Source OFF Leakage I _S (OFF)	±0.01	±0.35	nA typ	V _{DD} = +3.3 V V _S = 3 V/1 V, V _D = 1 V/3 V, Test Circuit 2
	±0.25		nA max	
Channel ON Leakage I _D , I _S (ON)	±0.01	±0.35	nA typ	V _S = V _D = 1 V, or V _S = V _D = 3 V, Test Circuit 3
	±0.25		nA max	
DIGITAL INPUTS				
Input High Voltage, V _{INH}	0.005	2.0	V min	V _{IN} = V _{INL} or V _{INH}
Input Low Voltage, V _{INL}		0.4	V max	
Input Current				
I _{INL} or I _{INH}		±0.1	μA typ μA max	
DYNAMIC CHARACTERISTICS ²				
t _{ON}	16	24	ns typ	R _L = 300 Ω, C _L = 35 pF V _S = 2 V, Test Circuit 4
			ns max	
t _{OFF}	4	7	ns typ	R _L = 300 Ω, C _L = 35 pF V _S = 2 V, Test Circuit 4
			ns max	
Break-Before-Make Time Delay, t _D	8	1	ns typ	R _L = 300 Ω, C _L = 35 pF V _{S1} = V _{S2} = 2 V, Test Circuit 5
			ns min	
Off Isolation	−67		dB typ	R _L = 50 Ω, C _L = 5 pF, f = 10 MHz R _L = 50 Ω, C _L = 5 pF, f = 1 MHz, Test Circuit 6
	−87		dB typ	
Channel-to-Channel Crosstalk	−62		dB typ	R _L = 50 Ω, C _L = 5 pF, f = 10 MHz R _L = 50 Ω, C _L = 5 pF, f = 1 MHz, Test Circuit 7
	−82		dB typ	
Bandwidth −3 dB	200		MHz typ	R _L = 50 Ω, C _L = 5 pF, Test Circuit 8
C _S (OFF)	7		pF typ	
C _D , C _S (ON)	27		pF typ	
POWER REQUIREMENTS				
I _{DD}	0.001	1.0	μA typ	V _{DD} = +3.3 V Digital Inputs = 0 V or 3 V
			μA max	

NOTES

¹Temperature ranges are as follows: B Version, -40°C to $+85^{\circ}\text{C}$.²Guaranteed by design, not subject to production test.

Specifications subject to change without notice.

ADG719

ABSOLUTE MAXIMUM RATINGS¹

(T_A = +25°C unless otherwise noted)

V _{DD} to GND	−0.3 V to +7 V
Analog, Digital Inputs ²	−0.3 V to V _{DD} + 0.3 V or 30 mA, Whichever Occurs First
Peak Current, S or D	100 mA (Pulsed at 1 ms, 10% Duty Cycle max)
Continuous Current, S or D	30 mA
Operating Temperature Range	
Industrial (B Version)	−40°C to +85°C
Storage Temperature Range	−65°C to +150°C
Junction Temperature	+150°C
μSOIC Package, Power Dissipation	315 mW
θ _{JA} Thermal Impedance	206°C/W
θ _{JC} Thermal Impedance	44°C/W
SOT-23 Package, Power Dissipation	282 mW
θ _{JA} Thermal Impedance	229.6°C/W
θ _{JC} Thermal Impedance	91.99°C/W
Lead Temperature, Soldering	
Vapor Phase (60 sec)	+215°C
Infrared (15 sec)	+220°C
ESD	1 kV

NOTES

¹Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Only one absolute maximum rating may be applied at any one time.


²Overvoltages at IN, S or D will be clamped by internal diodes. Current should be limited to the maximum ratings given.

Table I. Truth Table


ADG719 IN	Switch S1	Switch S2
0	ON	OFF
1	OFF	ON

PIN CONFIGURATIONS

**6-Lead SOT-23
(RT-6)**



**8-Lead μSOIC
(RM-8)**



ORDERING GUIDE

Model	Temperature Range	Brand*	Package Description	Package Option
ADG719BRM	−40°C to +85°C	S5B	μSOIC (microSmall Outline IC)	RM-8
ADG719BRT	−40°C to +85°C	S5B	SOT-23 (Plastic Surface Mount)	RT-6

*Brand = Due to package size limitations, these three characters represent the part number.

CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although the ADG719 features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.

TERMINOLOGY

V _{DD}	Most Positive Power Supply Potential.
GND	Ground (0 V) Reference.
S	Source Terminal. May be an input or output.
D	Drain Terminal. May be an input or output.
IN	Logic Control Input.
R _{ON}	Ohmic resistance between D and S.
ΔR _{ON}	On resistance match between any two channels i.e., R _{ON} max – R _{ON} min.
R _{FLAT(ON)}	Flatness is defined as the difference between the maximum and minimum value of on resistance as measured over the specified analog signal range.
I _S (OFF)	Source Leakage Current with the switch “OFF.”
I _D , I _S (ON)	Channel Leakage Current with the switch “ON.”
V _D (V _S)	Analog Voltage on Terminals D, S.
C _S (OFF)	“OFF” Switch Source Capacitance.
C _D (OFF)	“OFF” Switch Drain Capacitance.
C _D , C _S (ON)	“ON” Switch Capacitance.
t _{ON}	Delay between applying the digital control input and the output switching on.
t _{OFF}	Delay between applying the digital control input and the output switching off.
t _D	“OFF” time or “ON” time measured between the 90% points of both switches, when switching from one address state to another.
Crosstalk	A measure of unwanted signal that is coupled through from one channel to another as a result of parasitic capacitance.
Off Isolation	A measure of unwanted signal coupling through an “OFF” switch.
Bandwidth	The frequency at which the output is attenuated by −3 dBs.
On Response	The frequency response of the “ON” switch.
On Loss	The voltage drop across the “ON” switch seen on the On Response vs. Frequency plot as how many dBs the signal is away from 0 dB at very low frequencies.



Typical Performance Characteristics—ADG719




Figure 1. On Resistance as a Function of V_D (V_S) Single Supplies




Figure 4. Supply Current vs. Input Switching Frequency




Figure 2. On Resistance as a Function of V_D (V_S) for Different Temperatures $V_{DD} = 3V$




Figure 5. Off Isolation vs. Frequency




Figure 3. On Resistance as a Function of V_D (V_S) for Different Temperatures $V_{DD} = 5V$




Figure 6. Crosstalk vs. Frequency






Figure 7. On Response vs. Frequency


Test Circuits




Test Circuit 1. On Resistance




Test Circuit 2. Off Leakage




Test Circuit 3. On Leakage




Test Circuit 4. Switching Times




Test Circuit 5. Break-Before-Make Time Delay, t_D



Test Circuit 6. Off Isolation



Test Circuit 7. Channel-to-Channel Crosstalk



Test Circuit 8. Bandwidth

APPLICATIONS INFORMATION

The ADG719 belongs to Analog Devices' new family of CMOS switches. This series of general purpose switches have improved switching times, lower on resistance, higher bandwidths, low power consumption and low leakage currents.

ADG719 Supply Voltages

Functionality of the ADG719 extends from +1.8 V to +5.5 V single supply, which makes it ideal for battery powered instruments, where important design parameters are power efficiency and performance.

It is important to note that the supply voltage effects the input signal range, the on resistance and the switching times of the part. By taking a look at the typical performance characteristics and the specifications, the effects of the power supplies can be clearly seen.

For $V_{DD} = +1.8$ V operation, R_{ON} is typically 40 Ω over the temperature range.

On Response vs. Frequency

Figure 8 illustrates the parasitic components that affect the ac performance of CMOS switches (the switch is shown surrounded by a box). Additional external capacitances will further degrade some performance. These capacitances affect feedthrough, crosstalk and system bandwidth.




Figure 8. Switch Represented by Equivalent Parasitic Components

The transfer function that describes the equivalent diagram of the switch (Figure 8) is of the form $A(s)$ shown below.

$$A(s) = R_T \left[\frac{s(R_{ON} C_{DS}) + 1}{s(R_T R_{ON} C_T) + 1} \right]$$

where:

$$R_T = R_{LOAD} / (R_{LOAD} + R_{ON})$$

$$C_T = C_{LOAD} + C_D + C_{DS}$$

The signal transfer characteristic is dependent on the switch channel capacitance, C_{DS} . This capacitance creates a frequency zero in the numerator of the transfer function $A(s)$. Because the switch on resistance is small, this zero usually occurs at high frequencies. The bandwidth is a function of the switch output capacitance combined with C_{DS} and the load capacitance. The frequency pole corresponding to these capacitances appears in the denominator of $A(s)$.

The dominant effect of the output capacitance, C_D , causes the pole breakpoint frequency to occur first. Therefore, in order to maximize bandwidth a switch must have a low input and output capacitance and low on resistance. The On Response vs. Frequency plot for the ADG719 can be seen in Figure 7.

Off Isolation

Off isolation is a measure of the input signal coupled through an off switch to the switch output. The capacitance, C_{DS} , couples the input signal to the output load, when the switch is off as shown in Figure 9.





Figure 9. Off Isolation Is Affected by External Load Resistance and Capacitance

The larger the value of C_{DS} , larger values of feedthrough will be produced. The typical performance characteristic graph of Figure 5 illustrates the drop in off isolation as a function of frequency. From dc to roughly 200 kHz, the switch shows better than -95 dB isolation. Up to frequencies of 10 MHz, the off isolation remains better than -67 dB. As the frequency increases, more and more of the input signal is coupled through to the output. Off isolation can be maximized by choosing a switch with the smallest C_{DS} as possible. The values of load resistance and capacitance affect off isolation also, as they contribute to the coefficients of the poles and zeros in the transfer function of the switch when open.

$$A(s) = \left[\frac{s(R_{LOAD} C_{DS})}{s(R_{LOAD})(C_{LOAD} + C_D + C_{DS}) + 1} \right]$$

OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

8-Lead μ SOIC
(RM-8)6-Lead Plastic Surface Mount Package
(RT-6)