

40-Channel Symmetric Row Driver

Features


- ▶ HVCMOS® technology
- ▶ Symmetric row drive (reduces latent imaging in ACTFEL displays)
- ▶ Output voltage up to +240V
- ▶ Low power level shifting
- ▶ Source/sink current minimum 70mA
- ▶ Shift register speed 3MHz
- ▶ Pin-programmable shift direction (DIR, SHIFT)

General Description

The HV72 is a low-voltage serial to high-voltage parallel converters with push-pull outputs. It is especially suitable for use as a symmetric row driver in AC thin-film electroluminescent (ACTFEL) displays.

When the data reset pin (DRIO) is at logic high, it will reset all the outputs of the internal shift register to zero. At the same time, the output of the shift register will start shifting a logic high from the least significant bit to the most significant bit. The DRIO can be triggered at any time. The DIR and SHIFT pins control the direction of data shift through the device. When DIR is at logic high, DRIOA is the input and DRIOB is the output. When DIR is grounded, DRIOB is the input and the DRIOA is the output. See the Output Sequence Operation Table for output sequence. The \overline{POL} and \overline{OE} pins perform the polarity select and output enable function respectively. Data is loaded on the low to high transition of the clock. A logic high will cause the output to swing to V_{PP} if \overline{POL} is high, or to GND if \overline{POL} is low. All outputs will be in High-Z state if \overline{OE} is at logic high. Data output buffers are provided for cascading devices.

Functional Block Diagram



Ordering Information

Device	Package Options
	64-Lead PQFP
HV7224	HV7224PG-G

-G indicates package is RoHS compliant ("Green")



Absolute Maximum Ratings

Parameter	Value
Supply voltage, V_{DD}	-0.5V to +7.0V
Supply voltage, V_{PP}	-0.5V to +260V
Logic input levels	-0.5V to $V_{DD} + 0.5V$
Continuous total power dissipation ¹	1200mW
Operating temperature range	-40°C to +85°C
Storage temperature range	-65°C to +150°C
Lead temperature 1.6mm from case for 10 seconds	260°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

Note: 1. For operation above 25°C ambient derate linearly to maximum operating temperature at 20mW/°C.

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Units
V_{DD}	Logic supply voltage	4.5	5.5	V
V_{PP}	High voltage supply ¹	0	240	V
V_{IH}	High-level input voltage	0.7 V_{DD}	V_{DD}	V
V_{IL}	Low-level input voltage	0	0.2 V_{DD}	V
f_{CLK}	Clock frequency	-	3.0	MHz
T_A	Operating free-air temperature	-40	+85	°C
I_O	High voltage output current	-	±70	mA
I_{OD}	Allowable pulsed current through output diode	-	±300	mA


Note: 1. Output will not switch at $V_{PP} = 0V$.

Power-up sequence should be the following:


1. Connect ground.
2. Apply V_{DD} .
3. Set all inputs (Data, CLK, Enable, etc.) to a known state.
4. Apply V_{PP} .
5. The V_{PP} should not drop below V_{DD} or float during operation.

Power-down sequence should be the reverse of the above.

Pin Configuration



Product Marking



64-Lead PQFP (PG)

DC Electrical Characteristics

(over recommended operating conditions of $V_{DD} = 5V$, $V_{PP} = 240V$, and $T_A = 25^\circ C$ unless noted)

Symbol	Parameter	Min	Max	Units	Conditions	
I_{DD}	V_{DD} supply current	-	10	mA	$f_{CLK} = 3.0MHz$	
I_{PP}	High voltage supply current	-	2.0	mA	All outputs low or High-Z	
		-	4.0	mA	One output high ¹	
I_{DDQ}	Quiescent V_{DD} supply current	-	100	μA	All $V_{IN} = GND$ or V_{DD}	
V_{OH}	High level output	HV _{OUT}	190	-	V	$I_O = -70mA$
		Data out	4.5	-	V	$I_O = -100\mu A$
V_{OL}	Low level output	HV _{OUT}	-	50	V	$I_O = +70mA$
		Data out	-	0.5	V	$I_O = +100\mu A$
I_{IH}	High-level logic input current	-	1.0	μA	$V_{IH} = V_{DD}$	
I_{IL}	Low-level logic input current	-	-1.0	μA	$V_{IL} = 0V$	
I_{SAT}	Saturation current HV _{OUT}	P-channel	-80	-	mA	---
		N-channel	75	-	mA	---

Note:

1. Only one output can be turned on at a time.


AC Electrical Characteristics

Symbol	Parameter	Min	Max	Units	Conditions
f_{CLK}	Clock frequency	-	3.0	MHz	Per register, $C_L = 15pF$
$t_{W(H/L)}$	Clock width high or low	150	-	ns	---
t_{SUD}	Data set-up time before clock rises	50	-	ns	---
t_{HD}	Data hold time after clock rises	50	-	ns	---
t_{SUC}	HV _{OUT} delay from clock rises (Hi-Z to H or L)	-	1.0	μs	$C_L = 330pF // R_L = 10k\Omega$
t_{SUE}	HV _{OUT} delay from $\overline{\text{Output Enable}}$ falls	-	600	ns	$C_L = 330pF // R_L = 10k\Omega$
t_{HC}	HV _{OUT} delay from clock rises (H or L to Hi-Z)	-	2.0	μs	$C_L = 330pF // R_L = 10k\Omega$
t_{HE}	HV _{OUT} delay from $\overline{\text{Output Enable}}$ rises	-	600	ns	$C_L = 330pF // R_L = 10k\Omega$
t_{DHL}	Delay time clock to data output falls*	-	250	ns	$C_L = 15pF$
t_{DLH}	Delay time clock to data output rises*	-	250	ns	$C_L = 15pF$
t_{ONF}	HV _{OUT} fall time	-	2.0	μs	$C_L = 330pF // R_L = 10k\Omega$
t_{ONR}	HV _{OUT} rise time	-	2.0	μs	$C_L = 330pF // R_L = 10k\Omega$
t_{POW}	POL pulse width	3.0	-	μs	---
t_{OEW}	$\overline{\text{Output Enable}}$ pulse width	3.0	-	μs	---
SR	Slew rate, V_{PP} or GND	-	45	V/ μs	One active output driving 4.7nF load


Note:

* The delay is measured from the trailing edge of the clock but the data is triggered by the rising edge of the clock. There is an internal delay for the data output which is equal to t_{WH} . Therefore the delay is measured from the trailing edge of the clock.

Input and Output Equivalent Circuits



Switching Waveforms



Function Table

I/O Relations	Inputs					HV Outputs
	CLK	DIR	S/R DATA	$\overline{\text{POL}}$	$\overline{\text{OE}}$	
O/P HIGH	X	X	H	H	L	H
OP OFF	X	X	L	X	L	HIGH-Z
OP LOW	X	X	H	L	L	L
OP OFF	X	X	X	X	H	All O/P HIGH-Z

Notes:

H = logic high level, L = logic low level, X = irrelevant

Data input (DR_{IO}) loaded on the low-to-high transition of the clock.

Only one active output can be set at a time.

Output Sequence Operation Table

DIR	Shift	Data Reset In	Data Reset Out	HV _{OUT} # Sequence	Direction
L	L	DR_{IOB}	$\text{DR}_{\text{IOA}} 1$	40 → 1	
H	L	DR_{IOA}	$\text{DR}_{\text{IOB}} 2$	1 → 40	
L	H	DR_{IOB}	$\text{DR}_{\text{IOA}} 1$	20 → 1 → 40 → 21	
H	H	DR_{IOA}	$\text{DR}_{\text{IOB}} 2$	21 → 40 → 1 → 20	

Notes:

* Reference to package outline or chip layout drawing.

1. DR_{IOA} is DR_{IOB} delayed by 40 clock pulses.

2. DR_{IOB} is DR_{IOA} delayed by 40 clock pulses.

Pin Descriptions (64-Lead PQFP - PG) Option A

Pin #	Function	Pin #	Function	Pin #	Function	Pin #	Function
1	HVOUT1/40	17	HVOUT17/24	33	N/C	49	HVOUT25/16
2	HVOUT2/39	18	HVOUT18/23	34	DRIOB	50	HVOUT26/15
3	HVOUT3/38	19	HVOUT19/22	35	\overline{OE}	51	HVOUT27/14
4	HVOUT4/37	20	HVOUT20/21	36	N/C	52	HVOUT28/13
5	HVOUT5/36	21	VPP	37	\overline{POL}	53	HVOUT29/12
6	HVOUT6/35	22	N/C	38	N/C	54	HVOUT30/11
7	HVOUT7/34	23	GND (Power)	39	VDD	55	HVOUT31/10
8	HVOUT8/33	24	GND (Logic)	40	N/C	56	HVOUT32/9
9	HVOUT9/32	25	DIR	41	GND (Logic)	57	HVOUT33/8
10	HVOUT10/31	26	VDD	42	GND (Power)	58	HVOUT34/7
11	HVOUT11/30	27	CLK	43	N/C	59	HVOUT35/6
12	HVOUT12/29	28	N/C	44	VPP	60	HVOUT36/5
13	HVOUT13/28	29	SHIFT	45	HVOUT21/20	61	HVOUT37/4
14	HVOUT14/27	30	N/C	46	HVOUT22/19	62	HVOUT38/3
15	HVOUT15/26	31	DRIOA	47	HVOUT23/18	63	HVOUT39/2
16	HVOUT16/25	32	N/C	48	HVOUT24/17	64	HVOUT40/1

Note:

Pin designation for DIR H/L, Shift = L

Example: For DIR = H, pin 1 is HVOUT1

For DIR = L, pin 1 is HVOUT40

Pin Descriptions (64-Lead PQFP - PG) Option B

Pin #	Function	Pin #	Function	Pin #	Function	Pin #	Function
1	HVOUT20/21	17	HVOUT4/37	33	N/C	49	HVOUT36/5
2	HVOUT19/22	18	HVOUT3/38	34	DRIOB	50	HVOUT35/6
3	HVOUT18/23	19	HVOUT2/39	35	\overline{OE}	51	HVOUT34/7
4	HVOUT17/24	20	HVOUT1/40	36	N/C	52	HVOUT33/8
5	HVOUT16/25	21	VPP	37	\overline{POL}	53	HVOUT32/9
6	HVOUT15/26	22	N/C	38	N/C	54	HVOUT31/10
7	HVOUT14/27	23	GND (Power)	39	VDD	55	HVOUT30/11
8	HVOUT13/28	24	GND (Logic)	40	N/C	56	HVOUT29/12
9	HVOUT12/29	25	DIR	41	GND (Logic)	57	HVOUT28/13
10	HVOUT11/30	26	VDD	42	GND (Power)	58	HVOUT27/14
11	HVOUT10/31	27	CLK	43	N/C	59	HVOUT26/15
12	HVOUT9/32	28	N/C	44	VPP	60	HVOUT25/16
13	HVOUT8/33	29	SHIFT	45	HVOUT40/1	61	HVOUT24/17
14	HVOUT7/34	30	N/C	46	HVOUT39/2	62	HVOUT23/18
15	HVOUT6/35	31	DRIOA	47	HVOUT38/3	63	HVOUT22/19
16	HVOUT5/36	32	N/C	48	HVOUT37/4	64	HVOUT21/20


Note:

Pin designation for DIR H/L, Shift = H


Example: For DIR = H, pin 1 is HVOUT20

For DIR = L, pin 1 is HVOUT21


64-Lead PQFP Package Outline (PG)
20x14mm body, 3.4mm height (max.), 0.80mm pitch, 3.9mm footprint



Top View



View B



Side View

Note 1:

A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier may be either a mold, or an embedded metal or marked feature.

Symbol	A	A1	A2	b	D	D1	E	E1	e	L	L1	L2	L3	θ	θ1	
Dimension (mm)	MIN	2.80	0.25	2.55	0.30	21.70	19.80	17.65	13.80	0.80 BSC	0.73	1.95 REF	0.25 BSC	0.55 REF	0°	5°
	NOM	-	-	2.80	-	21.95	20.00	17.90	14.00		0.88				3.5°	-
	MAX	3.40	-	3.05	0.45	22.20	20.20	18.15	14.20		1.03				7°	16°

Modified Version of JEDEC Registration MO-112, Variation CB-1, Issue B, Sept.95.

Drawings not to scale.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell its products for use in such applications, unless it receives an adequate "product liability indemnification insurance agreement". **Supertex** does not assume responsibility for use of devices described and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the **Supertex** website: <http://www.supertex.com>.