

Thick Surface Mounts - BMATM3 Series

3/8" hole; 1-1/8"-18 thread; thick plate; can be used for metal thickness of 1/32"-1/2"

Model	Length of Coax	Coax	Connector	Type
BMATM338	N/A	None	None	N/A
BMATM3-NC	17'	RG-58/U	None	N/A
BMATM3CP	17'	RG-58/U	Silver Plated PL259	Crimp
BMATM3	17'	RG-58/U	Silver Plated PL259	Solder
BMATM3MSMA	17'	RG-58/U	SMA	Crimp
BMATM3PL	17'	RG-58/U	Mini-UHF	Crimp
BMAT3ML195PL	12'	PFP195	Mini-UHF	N/A



BMATM338

* Connector is installed on these mounts only. For all other mounts, connectors can be attached for an additional charge.

MTPM Series

5/8" hole; 1-1/8"-18 thread; thick plate mount

Model	Coax Assembly	Connector
MTPM	Sold separately	UG363/U
MTPM800	Sold separately	N Female
MTPMHF*	Sold separately	N Female

*High frequency mobile mount.



MTPM



MVP

MVP/Vandal Proof Mount

5/8" hole; 1-1/8"-18 thread; thick plate mount

Model	Coax Assembly	Connector
MVP	Sold separately	M to N Female

* Connector is installed on these mounts only. For all other mounts, connectors can be attached for an additional charge.