

Thick Surface Mounts - BMATM3 Series

3/8" hole; 1-1/8"-18 thread; thick plate; can be used for metal thickness of 1/32"-1/2"

| Model | Length of Coax | Coax | Connector | Type |
|--------------|----------------|---------|---------------------|--------|
| BMATM338 | N/A | None | None | N/A |
| BMATM3-NC | 17' | RG-58/U | None | N/A |
| BMATM3CP | 17' | RG-58/U | Silver Plated PL259 | Crimp |
| BMATM3 | 17' | RG-58/U | Silver Plated PL259 | Solder |
| BMATM3MSMA | 17' | RG-58/U | SMA | Crimp |
| BMATM3PL | 17' | RG-58/U | Mini-UHF | Crimp |
| BMAT3ML195PL | 12' | PFP195 | Mini-UHF | N/A |



BMATM338

* Connector is installed on these mounts only. For all other mounts, connectors can be attached for an additional charge.

MTPM Series

5/8" hole; 1-1/8"-18 thread; thick plate mount

| Model | Coax Assembly | Connector |
|---------|-----------------|-----------|
| MTPM | Sold separately | UG363/U |
| MTPM800 | Sold separately | N Female |
| MTPMHF* | Sold separately | N Female |

*High frequency mobile mount.



MTPM



MVP

MVP/Vandal Proof Mount

5/8" hole; 1-1/8"-18 thread; thick plate mount

| Model | Coax Assembly | Connector |
|-------|-----------------|---------------|
| MVP | Sold separately | M to N Female |

* Connector is installed on these mounts only. For all other mounts, connectors can be attached for an additional charge.