

Common Mode Filters(SMD) For High-speed Differential Signal Line

Conformity to RoHS Directive

TCM Series TCM0806G Type

FEATURES

- The TCM0806G (L0.85×W0.65×T0.40mm) is an ultra-compact common mode filter that is in the smallest class in the industry.
- By providing wide bandwidth (cutoff frequency: 3GHz) for differential mode, this product has almost no effect for highspeed differential signals and can suppress the radiated emission.
- This product contains no lead and supports lead-free soldering.

APPLICATIONS

- High speed interface(LVDS, IEEE1394 and USB2.0) in electronics devices.
- Portable audio, digital cellular phones, DVC, DSC, PDP/LCD/ DLP/PJ TVs, DVD players, notebook PCs, amusement machines, etc.

PRODUCT IDENTIFICATION

| TCM | 0806 | G - | 900 - | · 2P | - T |
|-----|------|-----|-------|------|-----|
| (1) | (2) | (3) | (4) | (5) | (6) |

- (1) Series name
- (2) Dimensions L×W
- (3) Product identification number
- (4) Impedance[at 100MHz] 900: 90Ω
- (5) Number of line 2P: 2-line
- (6) Packaging style
 T: ø180mm reel taping


TEMPERATURE RANGE

| Operating | −25 to +85°C | |
|-----------|--------------|--|


PACKAGING STYLE AND QUANTITIES

| Packaging style | Quantity |
|-----------------|-------------------|
| Taping | 10000 pieces/reel |

SHAPES AND DIMENSIONS/CIRCUIT DIAGRAM/RECOMMENDED PC BOARD PATTERN








ELECTRICAL CHARACTERISTICS

| Part No. | Common mode impedance (Ω) [100MHz] | DC resistance $(\Omega)[1 \text{ line}]$ | Rated current Idc(A)max. | Rated voltage Edc(V)max. | Insulation resistance $(M\Omega)$ min. |
|-----------------|---|--|--------------------------|-----------------------------|--|
| TCM0806G-350-2P | 35±30% | 1.15±30% | 0.10 | 10 | 10 |
| TCM0806G-650-2P | 65±20% | 2.50±30% | 0.10 | 10 | 10 |
| TCM0806G-900-2P | 90±20% | 2.70±30% | 0.10 | 10 | 10 |

- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
- All specifications are subject to change without notice.



TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS



[•] All specifications are subject to change without notice.