

180W, Rugged DC/DC Industrial Converter BAP 180-FT Series

- Rugged industrial quality
- Single regulated and adjustable output
- Full electronic protection
- Field-proven design in a wide range of applications
- N+1 redundancy available as option
- Plug-in (Eurocard) version available



This rugged, industrial quality DC/DC converter uses field-proven topology to generate 180W output power. It is a simpler version of the field proven BAP 236 series with cycling type overload protection. Cooling is via baseplate to a heatsinking surface and by natural convection. Low component count, large design headrooms, and the use of components with established reliability result in a high MTBF. An optional built-in redundancy diode allows for parallel and N+1 operation. Additional ruggedizing and conformal coating are available for applications requiring higher immunity to shock, vibration and humidity. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

Any single DC input from 12V to 125Vdc
Consult factory for other voltages

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

According to input voltage minimum of:
1000VDC input to chassis,
1500VDC input to output,
500VDC output to chassis

Standards

Designed to meet EN60950 and related standards.

EMI

EN 55022 Class A as a minimum

Switching Frequency

80KHz +/- 5KHz

Output Voltages

Any single DC output from 12V to 125Vdc (180W)
Consult factory for other voltages

Redundancy diode

Available as option

Line/Load Regulation

± 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple / Noise

Better than 1% of output voltage peak to peak or 0.2% Vrms (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown in case of insufficient cooling (self resetting)

Output Overvoltage Protection

Double regulator loop completely stable and independent of main loop

Efficiency

Typically 85% at full load depending on input/output combination

Operating Temperature Range

0 to + 60°C cold plate temperature for full specification
Extended temperature ranges available

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction via base plate and convection

Environmental Protection

Basic ruggedizing
Conformal coating as option

MTBF

160,000 hours at 45 °C
Demonstrated MTBF is significantly higher

Indicators

Green output ON LED visible through cooling slots

Control Input

None

Alarm Output

None on standard version
Form C available as option

Package/Dimensions (W x D x H)

F1: 112 x 51 x 201 mm
(4.4" x 2" x 7.9") including terminal block and flanges.
Mounting holes are clear

Weight

0.74 kg (1.64 lb)

Connections

9-pole barrier type terminal block, 3/8" spacing.

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa
Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com