


**DESCRIPTION**


ST2341M is the P-Channel logic enhancement mode power field effect transistor which is produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management, other battery powered circuits, and low in-line power loss are required. The product is in a very small outline surface mount package.

**PIN CONFIGURATION**  
**SOT-23-3L**



1.Gate 2.Source 3.Drain

**FEATURE**

- -20V/-2.8A,  $R_{DS(ON)} = 47m\Omega$  (Typ.) @VGS = -4.5V
- -20V/-2.8A,  $R_{DS(ON)} = 66m\Omega$  @VGS = -2.5V
- -20V/-2.3A,  $R_{DS(ON)} = 100m\Omega$  @VGS = -1.8V
- Super high density cell design for extremely low  $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOT-23-3L package design

**PART MARKING**  
**SOT-23-3L**


Y: Year Code A: Process Code



**ABSOLUTE MAXIMUM RATINGS** (Ta = 25°C Unless otherwise noted )

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V <sub>DSS</sub>	-20	V
Gate-Source Voltage	V <sub>GSS</sub>	±12	V
Continuous Drain Current (T <sub>J</sub> =150°C)	I <sub>D</sub>	T <sub>A</sub> =25°C -3.5	A
		T <sub>A</sub> =70°C -2.8	
Pulsed Drain Current	I <sub>DM</sub>	-12	A
Continuous Source Current (Diode Conduction)	I <sub>S</sub>	-1.0	A
Power Dissipation	P <sub>D</sub>	T <sub>A</sub> =25°C 1.25	W
		T <sub>A</sub> =70°C 0.80	
Operation Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>STG</sub>	-55/150	°C
Thermal Resistance-Junction to Ambient	R <sub>θJA</sub>	140	°C/W

**ELECTRICAL CHARACTERISTICS** (  $T_a = 25^\circ\text{C}$  Unless otherwise noted )

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.35		-0.9	V
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=-20V, V_{GS}=0V$			-1	uA
		$V_{DS}=-20V, V_{GS}=0V$ $T_J=55^\circ\text{C}$			-10	
On-State Drain Current	$I_{D(on)}$	$V_{DS}\leq -5V, V_{GS}=-4.5V$	-6			A
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-3.3A$		47		m $\Omega$
		$V_{GS}=-2.5V, I_D=-2.8A$		66		
		$V_{GS}=-1.8V, I_D=-2.3A$		00		
Forward Transconductance	$g_{fs}$	$V_{DS}=-5V, I_D=-4V$		3.0		S
Diode Forward Voltage	$V_{SD}$	$I_S=-1A, V_{GS}=0V$		-0.8	-1.2	V
<b>Dynamic</b>						
Total Gate Charge	$Q_g$	$V_{DS}=-6V$ $V_{GS}=-4.5V$ $I_D=-3.3A$		8.0	13	nC
Gate-Source Charge	$Q_{gs}$			1.2		
Gate-Drain Charge	$Q_{gd}$			2.2		
Input Capacitance	$C_{iss}$	$V_{DS}=-6.0V$ $V_{GS}=0V$ $F=1\text{MHz}$		700		pF
Output Capacitance	$C_{oss}$			160		
Reverse Transfer Capacitance	$C_{rss}$			120		
Turn-On Time	$t_{d(on)}$ $t_r$	$V_{DD}=-6V$ $R_L=6\Omega$ $I_D=-1.0A$ $V_{GEN}=-4.5V$ $R_G=6\Omega$		15	25	nS
				35	55	
Turn-Off Time	$t_{d(off)}$ $t_f$			60	90	
				40	40	



**ST2341M** 

P Channel Enhancement Mode MOSFET







-3.5A

---

**TYPICAL CHARACTERISTICS** (25°C Unless noted)






STANSON TECHNOLOGY  
120 Bentley Square, Mountain View, Ca 94040 USA  
[www.stansontech.com](http://www.stansontech.com)

*ST2341 2006. Rev. 1*




**TYPICAL CHARACTERISTICS** (25°C Unless noted)

STANSON TECHNOLOGY  
 120 Bentley Square, Mountain View, Ca 94040 USA  
 www.stansontech.com



## SOT-23-3L PACKAGE OUTLINE

STANSON TECHNOLOGY  
 120 Bentley Square, Mountain View, Ca 94040 USA  
[www.stansontech.com](http://www.stansontech.com)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°