


## N- and P-Channel 30-V (D-S) MOSFET


PRODUCT SUMMARY			
	$V_{DS}$ (V)	$r_{DS(on)}$ ( $\Omega$ )	$I_D$ (A)
N-Channel	30	0.032 @ $V_{GS} = 10$ V	4.3
		0.046 @ $V_{GS} = 4.5$ V	3.7
P-Channel	-30	0.043 @ $V_{GS} = -10$ V	-3.8
		0.073 @ $V_{GS} = -4.5$ V	-2.8

### FEATURES


- TrenchFET® Power MOSFETS



Ordering Information: Si6544BDQ-T1



N-Channel MOSFET



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)						
Parameter	Symbol	N-Channel		P-Channel		Unit
		10 sec	Steady State	10 sec	Steady State	
Drain-Source Voltage	$V_{DS}$	30		-30		V
Gate-Source Voltage	$V_{GS}$	$\pm 20$				
Continuous Drain Current ( $T_J = 150^\circ\text{C}$ ) <sup>a</sup>	$T_A = 25^\circ\text{C}$	4.3	3.7	-3.8	-3.8	A
	$T_A = 70^\circ\text{C}$	3.5	3.0	-3.0	-2.6	
Pulsed Drain Current	$I_{DM}$	20		-20		
Continuous Source Current (Diode Conduction) <sup>a</sup>	$I_S$	1.0	0.7	-1.0	-0.7	
Maximum Power Dissipation <sup>a</sup>	$T_A = 25^\circ\text{C}$	1.14	0.83	1.14	0.83	W
	$T_A = 70^\circ\text{C}$	0.73	0.53	0.73	0.53	
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to 150				$^\circ\text{C}$

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient <sup>a</sup>	$R_{thJA}$	$t \leq 10$ sec	88	110	$^\circ\text{C/W}$
		Steady State	120	150	
Maximum Junction-to-Foot (Drain)	$R_{thJF}$	65	80		

Notes

a. Surface Mounted on FR4 Board,  $t \leq 10$  sec.

SPECIFICATIONS (T <sub>J</sub> = 25 °C UNLESS OTHERWISE NOTED)							
Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
<b>Static</b>							
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA	N-Ch	1.0		3.0	V
		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250 μA	P-Ch	-1.0		-3.0	
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V	N-Ch P-Ch			±100 ±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 24 V, V <sub>GS</sub> = 0 V	N-Ch			1	μA
		V <sub>DS</sub> = -24 V, V <sub>GS</sub> = 0 V	P-Ch			-1	
		V <sub>DS</sub> = 24 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 55 °C	N-Ch			5	
		V <sub>DS</sub> = -24 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 55 °C	P-Ch			-5	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> ≥ 5 V, V <sub>GS</sub> = 10 V	N-Ch	20			A
		V <sub>DS</sub> ≥ -5 V, V <sub>GS</sub> = -10 V	P-Ch	-20			
Drain-Source On-State Resistance <sup>a</sup>	r <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 4.3 A	N-Ch		0.025	0.032	Ω
		V <sub>GS</sub> = -10 V, I <sub>D</sub> = -3.8 A	P-Ch		0.034	0.043	
		V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 3.7 A	N-Ch		0.037	0.046	
		V <sub>GS</sub> = -4.5 V, I <sub>D</sub> = -2.8 A	P-Ch		0.058	0.073	
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 15 V, I <sub>D</sub> = 4.3 A	N-Ch		11		S
		V <sub>DS</sub> = -15 V, I <sub>D</sub> = -3.8 A	P-Ch		11		
Diode Forward Voltage <sup>a</sup>	V <sub>SD</sub>	I <sub>S</sub> = 1.25 A, V <sub>GS</sub> = 0 V	N-Ch		0.77	1.1	V
		I <sub>S</sub> = -1.25 A, V <sub>GS</sub> = 0 V	P-Ch		-0.77	-1.1	
<b>Dynamic<sup>b</sup></b>							
Total Gate Charge	Q <sub>g</sub>	N-Channel V <sub>DS</sub> = 15 V, V <sub>GS</sub> = 10 V, I <sub>D</sub> = 4.3 A  P-Channel V <sub>DS</sub> = -15 V, V <sub>GS</sub> = -10 V, I <sub>D</sub> = -3.8 A	N-Ch		9.5	15	nC
			P-Ch		16	25	
Gate-Source Charge	Q <sub>gs</sub>		N-Ch		1.8		
			P-Ch		2.3		
Gate-Drain Charge	Q <sub>gd</sub>		N-Ch		1.55		
			P-Ch		4.5		
Gate Resistance	R <sub>g</sub>	N-Ch		0.45		Ω	
		P-Ch		8.8			
Turn-On Delay Time	t <sub>d(on)</sub>	N-Ch		13	25	ns	
		P-Ch		14	25		
Rise Time	t <sub>r</sub>	N-Ch		14	25		
		P-Ch		14	25		
Turn-Off Delay Time	t <sub>d(off)</sub>	N-Ch		30	50		
		P-Ch		40	65		
Fall Time	t <sub>f</sub>	N-Ch		10	20		
		P-Ch		30	50		
Source-Drain Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 1.25 A, di/dt = 100 A/μs	N-Ch		30	60	
		I <sub>F</sub> = -1.25 A, di/dt = 100 A/μs	P-Ch		30		







## Notes

- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

N-CHANNEL







#### TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

#### N-CHANNEL


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage



Single Pulse Power, Junction-to-Ambient



Safe Operating Area, Junction-to-Case







TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

N-CHANNEL

Normalized Thermal Transient Impedance, Junction-to-Ambient









Normalized Thermal Transient Impedance, Junction-to-Foot





**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**

**P-CHANNEL**







**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)**

**P-CHANNEL**


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage



Single Pulse Power, Junction-to-Ambient




Safe Operating Area, Junction-to-Case




**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**

**P-CHANNEL**

Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot







## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.