# Solid State Relay G3M

# 1, 2, 3 and 5 A single in-line package SSR

- Thin design for high-density PCB applications.
- DC input-AC output for up to a 5-A load.
- Two foot prints offer greater flexibility.
- Approved by UL and CSA.











# Ordering Information

To order: Select the part number and add the desired input voltage rating, (e.g., G3M-202P-US DC5)

Isolation	Input terminal pitch	Zero cross function	Indicator	Rated output load (Applicable output load)	Rated input voltage	Model
Phototriac	7.62 mm	Yes	No	2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)	5 VDC	G3M-202P-US
					12 VDC	
					24 VDC	
				3 A at 100 to 240 VAC	5 VDC	G3M-203P
				(3 A at 75 to 264 VAC)	12 VDC	
					24 VDC	
				5 A at 100 to 240 VAC	5 VDC	G3M-205P
	No	No		(5 A at 75 to 264 VAC)	12 VDC	
					24VDC	
				2 A at 100 to 120 VAC (2 A at 75 to 132 VAC)	5 VDC	G3M-102PL-US
					12 VDC	
					24 VDC	
				2 A at 100 to 240 VAC	5 VDC	G3M-202PL-US
			(2 A at 75 to 264 VAC)	12 VDC	1	
					24 VDC	1
			3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)	5 VDC	G3M-203PL	
				12 VDC		
					24 VDC	
				5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)	5 VDC	G3M-205PL
					12 VDC	7
					24 VDC	7

(This table continues on the next page.)

# **Ordering Information (continued)**

(2 A at 75 to 264 VAC)	Isolation	Input terminal pitch	Zero cross function	Indicator	Rated output load (Applicable output load)	Rated input voltage	Model
No    12 VDC   24 VDC   5 VDC   G3M-203P-4	Phototriac	5.08 mm	Yes	No		5 VDC	G3M-202P-US-4
No   S A at 100 to 240 VAC (3 A at 75 to 264 VAC)   5 VDC   12 VDC   24 VDC   24 VDC   24 VDC   24 VDC   12 VDC   24 VDC   12 VDC   24 VDC   25 V						12 VDC	
(3 A at 75 to 264 VAC)						24 VDC	
No    12 VDC						5 VDC	G3M-203P-4
S A at 100 to 240 VAC					(3 A at 75 to 264 VAC)	12 VDC	
(5 A at 75 to 264 VAC)   12 VDC   24 VDC						24 VDC	
No  2 A at 100 to 120 VAC (3 A at 75 to 132 VAC)  2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  4 VDC  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  4 VDC  4 VDC  5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  7 A at 75 to 264 VAC  8 A at 75 to 264 VAC  8 A at 75 to 264 VAC  8 A at 75 to 264 VAC  9 A at 75 to 264 V						5 VDC	G3M-205P-4
No  2 A at 100 to 120 VAC (3 A at 75 to 132 VAC)  2 A vDC  2 A vDC  2 A vDC  2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  24 VDC  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  4 VDC  5 A at 100 to 240 VAC 5 VDC  6 S VDC  7 S VDC  7 S VDC  7 S VDC  7 S VDC  8 S VDC  9 S VDC		No	No		(5 A at 75 to 264 VAC)	12 VDC	
(3 A at 75 to 132 VAC)  12 VDC  24 VDC  2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  24 VDC  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 A at 100 to 240 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  7 A at 75 to 264 VAC  8 A at						24 VDC	
2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  24 VDC  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)  5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)  5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)  5 A at 100 to 240 VAC (5 A at 75 to 264 VAC)  5 VDC  63M-203PL-4						5 VDC	G3M-102PL-US-4
2 A at 100 to 240 VAC (2 A at 75 to 264 VAC)  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  24 VDC  12 VDC  12 VDC  24 VDC  12 VDC  24 VDC  5 A at 100 to 240 VAC (24 VDC)  5 A at 100 to 240 VAC (5 VDC)  5 A at 100 to 240 VAC (5 VDC)  5 A at 100 to 240 VAC (5 VDC)  5 A at 75 to 264 VAC)  5 VDC  G3M-203PL-4						12 VDC	
(2 A at 75 to 264 VAC)  12 VDC  24 VDC  3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 VDC  12 VDC  12 VDC  24 VDC  5 A at 100 to 240 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC  5 VDC  6 A at 75 to 264 VAC						24 VDC	
3 A at 100 to 240 VAC (3 A at 75 to 264 VAC)  5 A at 100 to 240 VAC  24 VDC  24 VDC  24 VDC  5 A at 100 to 240 VAC  5 VDC  63M-203PL-4  65 A at 75 to 264 VAC  5 VDC  63M-205PL-4						5 VDC	G3M-202PL-US-4
3 A at 100 to 240 VAC (3 A at 75 to 264 VAC) 5 VDC 12 VDC 24 VDC 5 A at 100 to 240 VAC 5 VDC G3M-205PL-4						12 VDC	
(3 A at 75 to 264 VAC)  12 VDC  24 VDC  5 A at 100 to 240 VAC  (5 A at 75 to 264 VAC)  5 VDC  G3M-205PL-4						24 VDC	
5 A at 100 to 240 VAC 5 VDC G3M-205PL-4						5 VDC	G3M-203PL-4
5 A at 100 to 240 VAC 5 VDC G3M-205PL-4					(3 A at 75 to 264 VAC)	12 VDC	
(5 A at 75 to 264 V/AC)						24 VDC	
(5 A at 75 to 264 VAC) 12 VDC						5 VDC	G3M-205PL-4
						12 VDC	
24 VDC						24 VDC	

Note: 1.  $T\ddot{\text{U}}\text{V}$  marking is available with "-UTU" in place of "-US" on the part number.

2. VDE versions available. Contact your local OMRON representative.

$\sim$										
Ć.	n	$\sim$	$\sim$	18	10	$\sim$	+1	$\sim$	n	
S	L )	▭	ι.		и.	.a		( )	11	
$\overline{}$	$\sim$	$\overline{}$	•	• •	. •	_	•	$\overline{}$		_

# **■ RATINGS**

# Input

Rated voltage	Operating voltage	Impedance	Voltage levels	
			Must operate voltage	Must release voltage
5 VDC	4 to 6 VDC	300 Ω ±20%	4 VDC max.	1 VDC min.
12 VDC	9.6 to 14.4 VDC	800 Ω ±20%	9.6 VDC max.	
24 VDC	19.2 to 28.8 VDC	1.6 kΩ ±20%	19.2 VDC max.	

Note: Each model has 5-VDC, 12-VDC, and 24-VDC input versions.

# Output

Model	Rated voltage	Applicable load		
		Load voltage	Load current	Inrush current
G3M-102PL-US (-4)	100 to 120 VAC	75 to 132 VAC	0.1 to 2 A	30 A (60 Hz, 1 cycle)
G3M-202P(L)-US (-4)	100 to 240 VAC	75 to 264 VAC		
G3M-203P(L) (-4)			0.1 to 3 A	45 A (60 Hz, 1 cycle)
G3M-205P(L) (-4)			0.1 to 5 A	

# **■ CHARACTERISTICS**

Item	G3M-102PL-US (-4)	G3M-202P(L)-US (-4)	G3M-203P(L) (-4)	G3M-205P(L) (-4)			
Operate time	1 ms max. (1/2 of load power source cycle + 1 ms max. for G3M-202P, G3M-203P, G3M-205P)						
Release time	1/2 of load power source c	1/2 of load power source cycle + 1 ms max.					
Output ON voltage drop	1.6 V (RMS) max.						
Leakage current	2 mA max. (at 100 VAC)	2 mA max. (at 100 VAC) 5 mA max. (at 200 VAC)	1.5 mA (at 200 VAC)				
Insulation resistance	1,000 MΩ min. (at 500 VD	C)					
Dielectric strength	2,000 VAC, 50/60 Hz for 1 min 2,500 VAC, 50/60 Hz for 1 min						
Vibration resistance	Malfunction: 10 to 55 Hz, 1.5-mm double amplitude						
Shock resistance	Malfunction: 1,000 m/s <sup>2</sup> {a	Malfunction: 1,000 m/s <sup>2</sup> {approx. 100G}					
Ambient temperature	Operating: -30°C to 80°C (with no icing or condensation) Storage: -30°C to 100°C (with no icing or condensation)						
Approved standards	UL508 File No.E64562/CSA C22.2 (No.0, No.14) File No. LR35535 TÜV R9551055 (EN60950)						
Ambient humidity	Operating: 45% to 85%						
Weight	Approx. 15 g Approx. 25 g						

# **■** APPROVALS

# UL (File No. E64562)/CSA (File No. LR35535)

Input Voltage	SSR Type	Load Rating
5, 12, 24 VDC	With Suffixes 102 and US or UTU	2 A, 125 VAC, Resistive 250 W, 125 VAC, Tungsten 2 A FLA, 12 A LRA, 125 VAC
	With Suffixes 202 and US	2 A, 250 VAC, Resistive 500 W, 250 VAC, Tungsten 2 A FLA, 12 A LRA, 250 VAC
	With Suffixes 202 UTU, UTU-1, and UTU-2	2 A, 250 VAC, Resistive 250 W, 250 VAC, Tungsten 1 FLA, 6 LRA, 250 VAC
	With Suffixes 103 and US or UTU	3 A, 125 VAC, Resistive 375 W, 125 VAC, Tungsten 1.5 A FLA, 9 A LRA, 125 VAC
	With Suffixes 203 and US or UTU	3 A, 250 VAC, Resistive 750 W, 250 VAC, Tungsten 1.5 A FLA, 9 A LRA, 250 VAC
	With Suffix 105	5 A, 125 VAC, Resistive 625 W, 125 VAC, Tungsten 2.5 A FLA, 15 A LRA, 125 VAC
	With Suffix 205	5 A, 250 VAC, Resistive 1250 W, 250 VAC, Tungsten 2.5 A FLA, 15 A LRA, 250 VAC

# **Engineering Data**


# **Load Current vs. Temperature Ambient**

# G3M-203P(L)(-4) G3M-203P(L)(-4) G3M-203P(L)-US(-4) G3M-202P(L)-US(-4) G3M-202P(L)-US(-4) Ambient temperature (°C)


Load current (A)

# **Inrush Current Immunity**

Non-repetitive Reduce the current to 1/2 or less if the G3M is in repetitive operation.



# Load Current vs. Ambient Temperature (Close Mounting) G3M-205 (5-A Load)




- Thirty Relays are soldered to the PCB at each given spacing.
- Continuous power.


# **Dimensions**

Note: All units are in millimeters unless otherwise indicated.

# G3M-102PL-US(-4), G3M-202P(L)-US(-4) G3M-203P(L)(-4)










# G3M-205P(L)(-4)









\*Input terminal pitch of 5.08 mm is also available.

# **Precautions**

#### **Protective Element**

No overvoltage absorption element is built in. Therefore, if the G3M is connected to an inductive load, be sure to connect the overvoltage absorption element.

# **Omron Electronic Components, LLC**

Terms and Conditions of Sales

#### I. GENERAL

Definitions: The words used herein are defined as follows.

Terms: These terms and conditions

Seller: Omron Electronic Components LLC and its subsidiaries

The buyer of Products, including any end user in section III through VI Products and/or services of Seller (c) Buyer

Products:

Including: Including without limitation

Offer: Acceptance: These Terms are deemed part of all quotations, acknowledgments, invoices, purchase orders and other documents, whether electronic or in writing, relating to the sale of Products by Seller. Seller hereby objects to any Terms proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms.

Distributor: Any distributor shall inform its customer of the contents after and including section III of these Terms.

#### II. SALES

- Prices; Payment: All prices stated are current, subject to change without notice by Seller. Buyer agrees to pay the price in effect at time of shipment. Payments for Products received are due net 30 days unless otherwise stated in the invoice. Buyer shall have no right to set off any amounts against the amount owing in respect of this
- Discounts: Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (a) the invoice is paid according to Seller's payment terms and (b) Buyer has no past due amounts owing to Seller.
- Interest: Seller, at its option, may charge Buyer 1.5% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the stated
- Orders: Seller will accept no order less than 200 U.S. dollars net billing.
- Currencies: If the prices quoted herein are in a currency other than U.S. dollars, Buyer shall make remittance to Seller at the then current exchange rate most favorable to Seller; provided that if remittance is not made when due, Buyer will convert the amount to U.S. dollars at the then current exchange rate most favorable to Seller available during the period between the due date and the date remittance is actually made
- Governmental Approvals: Buyer shall be responsible for all costs involved in obtaining any government approvals regarding the importation or sale of the Products
- Taxes: All taxes, duties and other governmental charges (other than general real properly and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Seller or required to be collected directly or indirectly by Seller for the manufacture, production, sale, delivery, importation, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Seller.
- <u>Financial</u>: If the financial position of Buyer at any time becomes unsatisfactory to Seller, Seller reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Seller may (without liability and in addition to other remedies) cancel any unshipped portion of Products sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts.
- Cancellation; Etc: Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Seller fully against all costs or expenses arising in connection therewith.
- Force Majeure: Seller shall not be liable for any delay or failure in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or the requirements of any government authority
- Shipping: Delivery. Unless otherwise expressly agreed in writing by Seller:
   (a) All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Seller), at which point title to and all risk of loss of the Products shall pass from Seller to Buyer, provided that Seller shall retain a security interest in the Products until the full purchase price is paid by Buyer;
  - Delivery and shipping dates are estimates only; and
  - Seller will package Products as it deems proper for protection against normal handling and extra charges apply to special conditions.
- 12. Claims: Any claim by Buyer against Seller for shortage or damage to the Products occurring before delivery to the carrier must be presented in detail in writing to Seller within 30 days of receipt of shipment.

#### **III. PRECAUTIONS**

- Suitability: IT IS THE BUYER'S SOLE RESPONSIBILITY TO ENSURE THAT ANY OMRON PRODUCT IS FIT AND SUFFICIENT FOR USE IN A MOTORIZED VEHICLE APPLICATION. BUYER SHALL BE SOLELY RESPONSIBLE FOR DETERMINING APPROPRIATENESS OF THE PARTICULAR PRODUCT WITH RESPECT TO THE BUYER'S APPLICATION INCLUDING (A) ELECTRICAL OR ELECTRONIC COMPONENTS, (B) CIRCUITS, (C) SYSTEM ASSEMBLIES, (D) END PRODUCT, (E) SYSTEM, (F) MATÉRIALS OR SUBSTANCES OR (G) OPERATING ENVIRONMENT. Buyer acknowledges that it alone has determined that the Products will meet their requirements of the intended use in <u>all</u> cases. Buyer must know and observe all prohibitions of use applicable to the Product/s.
- <u>Use with Attention:</u> The followings are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible use of any Product, nor to imply that any use listed may be suitable for any Product:

- Outdoor use, use involving potential chemical contamination or electrical interference.
- Use in consumer Products or any use in significant quantities.
- Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- Systems, machines, and equipment that could present a risk to life or property. Prohibited Use: NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND
- THAT THE PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM. Motorized Vehicle Application: USE OF ANY PRODUCT/S FOR A MOTORIZED
- VEHICLE APPLICATION MUST BE EXPRESSLY STATED IN THE SPECIFICATION
- Programmable Products: Seller shall not be responsible for the Buyer's programming of a programmable Product.

# IV. WARRANTY AND LIMITATION

- Warranty: Seller's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Seller (or such other period expressed in writing by Seller). SELLER MAKES NO Warranty or representation, express or implied, about all OTHER WARRANTIES, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS.
- Buyer Remedy: Seller's sole obligation hereunder shall be to replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product or, at Seller's election, to repay or credit Buyer an amount equal to the purchase price of the Product; provided that there shall be no liability for Seller or its affiliates unless Seller's analysis confirms that the Products were handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Seller before shipment.

  <u>Limitation on Liability</u>. SELLER AND ITS AFFILIATES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES, LOSS OF
- PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. FURTHER, IN NO EVENT SHALL LIABILITY OF SELLER OR ITS AFFILITATES EXCEED THE INDIVIDUAL PRICE OF THE PRODUCT ON WHICH LIABILITY IS ASSERTED.
- Indemnities: Buyer shall indemnify and hold harmless Seller, its affiliates and its employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim, investigation, litigation or proceeding (whether or not Seller is a party) which arises or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the

#### V. INFORMATION; ETC.

- Intellectual Property: The intellectual property embodied in the Products is the exclusive property of Seller and its affiliates and Buyer shall not attempt to duplicate it in any way without the written permission of Seller. Buyer (at its own expense) shall indemnify and hold harmless Seller and defend or settle any action brought against Seller to the extent that it is based on a claim that any Product made to Buyer specifications infringed intellectual property rights of another party
- Property: Confidentiality: Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Seller. All information and materials supplied by Seller to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly prevent disclosure to any third party.
- Performance Data: Performance data is provided as a guide in determining suitability and does not constitute a warranty. It may represent the result of Seller's test conditions, and the users must correlate it to actual application requirements.
- Change In Specifications: Product specifications and description may be changed at any time based on improvements or other reasons. It is Seller's practice to change part numbers when published ratings or features are changed, or when significant engineering changes are made. However, some specifications of the Product may be changed without any notice.
- Errors And Omissions: The information on Seller's website or in other documentation has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.
- Export Controls: Buyer shall comply with all applicable laws, regulations and licenses regarding (a) export of the Products or information provided by Seller, (b) sale of Products to forbidden or other proscribed persons or organizations; (c) disclosure to non-citizens of regulated technology or information.

#### VI. MISCELLANEOUS

- Waiver: No failure or delay by Seller in exercising any right and no course of dealing between Buyer and Seller shall operate as a waiver of rights by Seller
- Assignment: Buyer may not assign its rights hereunder without Seller's written consent. Law: These Terms are governed by Illinois law (without regard to conflict of laws).
- Federal and state courts in Illinois have exclusive jurisdiction for any dispute
- Amendment: These Terms constitute the entire agreement between Buyer and Seller relating to the Products, and no provision may be changed or waived unless in writing signed by the parties.
- Severability: If any provision hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision.

# Certain Precautions on Specifications and Use

- <u>Suitability of Use</u>. Seller shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in Buyer's application or use of the Product. At Buyer's request, Seller will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a non-exhaustive list of applications for which particular attention must
  - Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.
  - Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.

  - Use in consumer products or any use in significant quantities. Systems, machines and equipment that could present a risk to life or property. Please know and observe all prohibitions of use applicable

notes the product.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THATTHE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIP-MENT OR SYSTEM.

- Programmable Products. Seller shall not be responsible for the user's programming of a programmable product, or any consequence thereof.
   Performance Data. Performance data given in this publication is provided
- as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Seller's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to Seller's Warranty and Limitations of Liability.
- Change in Specifications. Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Seller representative at any time to confirm actual specifications of pur-
- Errors and Omissions. The information in this publication has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors, or omis
- sions.

  RoHS Compliance. Where indicated, our products currently comply, to the best of our knowledge as of the date of this publication, with the requirements of the European Union's Directive on the Restriction of certain Hazardous Substances ("RoHS"), although the requirements of RoHS do not take effect until July 2006. These requirements may be subject to change. Please consult our website for current information.



Complete "Terms and Conditions of Sale" for product purchase and use are on Omron's website at www.omron.com/oei - under the "About Us" tab, in the Legal Matters section.

**ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.**To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON ELECTRONIC **COMPONENTS LLC** 55 E. Commerce Drive, Suite B Schaumburg, IL 60173

847-882-2288

Cat. No. J01C-E-01

01/07

**OMRON ON-LINE** 

Global - http://www.omron.com USA - http://www.omron.com/oei Canada - http://www.omron.ca

Specifications subject to change without notice

Printed in USA