

## KVR266X72C25/1G 1024MB 128 x 72-Bit DDR266 CL2.5 ECC 184-Pin DIMM Module


### DESCRIPTION:

This document describes ValueRAM's 128M x 72-bit (1024MB), CAS Latency 2.5 SDRAM (Synchronous DRAM) DDR266 ECC memory module. The components on this module include eighteen 64M x 8-bit (16M x 8-bit x 4 Bank / 133MHz, 7.5ns, CL2.5 components) SDRAM in TSOP packages. This 184-pin DIMM uses gold contact fingers and requires +2.5V. The electrical and mechanical specifications are as follows:

### FEATURES:

✓ Clock Cycle Time (tCK)	7.5ns (min.) / 12ns (max.)
✓ Row Cycle Time (tRC)	65ns (min.)
✓ Refresh Row Cycle Time (tRFC)	75ns (min.)
✓ Row Active Time (tRAS)	45ns (min.) / 120,000ns (max.)
✓ Single Power Supply of	+2.5V (+/- .25V)
✓ Power (IDD0)	5.850 W (operating)
✓ UL Rating	94 V - 0

**Note:** The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.250" (31.75mm).



**Figure 1: KVR266X72C25/1G 184-Pin DDR SDRAM Module**