

PB4314 Series


Specifications:

Parameters	Units	PB4314A12AP
▶ Min Sound Pressure Level at 30cm	dBA	100
Rated Voltage	Vdc	12
Operating Voltage	Vdc	3 - 20
Resonance Frequency	Hz	2800 ± 500
▶ Max Operating Current	mA	12
Tone	-	Continuous
Operating Temperature	°C	-20 - +60
Case Material	-	ABS
Weight	g	12



▶ Value applying rated voltage

Unit: mm • Tolerance: ±0.5mm



PB4333 Series

Specifications:

Parameters	Units	PB4333A12PNP	PB4333A24CNP	PB4333A12DNP
▶ Min Sound Pressure Level at 30cm	dBA	100	95	100
Rated Voltage	Vdc	12	24	12
Operating Voltage	Vdc	3 - 28	7 - 30	3 - 28
Resonance Frequency	Hz	2900 ± 500	2900 ± 500	2900 ± 500
▶ Max Operating Current	mA	10	12	10
Tone	-	Pulse	Continuous	Dual (C or P)
Operating Temperature	°C	-40 - +85	-40 - +85	-40 - +85
Case Material	-	Noryl	Noryl	Noryl
Weight	g	39	39	39



▶ Value applying rated voltage

Unit: mm • Tolerance: ±0.5mm

