

PB4435 Series

Specifications:

Parameters	Units	PB4435A12CAP	PB4435A12PAP	PB4435A12FAP	PB4435A12DAP
▶ Min Sound Pressure Level at 30cm	dBA	90	90	95	95
Rated Voltage	Vdc	12	12	12	12
Operating Voltage	Vdc	1.5 - 30	1.5 - 15	1.5 - 20	3 - 18
Resonance Frequency	Hz	2900 ± 500	2900 ± 500	2900 ± 500	2900 ± 500
▶ Max Operating Current	mA	8	20	20	20
Tone	-	Continuous	Pulse	Fast Pulse	Dual (C or P)
Operating Temperature	°C	-20 - +60	-20 - +60	-20 - +60	-20 - +60
Case Material	-	ABS	ABS	ABS	ABS
Weight	g	35	35	35	35



Specifications:

Parameters	Units	PB4435A24CAP	PB4435A24PAP	PB4435A24FAP	PB4435A24DAP
▶ Min Sound Pressure Level at 30cm	dBA	100	100	100	100
Rated Voltage	Vdc	24	24	24	24
Operating Voltage	Vdc	3 - 28	6 - 28	4 - 28	6 - 28
Resonance Frequency	Hz	2900 ± 500	2900 ± 500	2900 ± 500	2900 ± 500
▶ Max Operating Current	mA	22	30	20	40
Tone	-	Continuous	Pulse	Fast Pulse	Dual (C or P)
Operating Temperature	°C	-20 - +60	-20 - +60	-20 - +60	-20 - +60
Case Material	-	ABS	ABS	ABS	ABS
Weight	g	35	35	35	35

Unit: mm • Tolerance: ±0.5mm

▶ Value applying rated voltage

