



PRELIMINARY

Solid State Devices, Inc.

14701 Firestone Blvd \* La Mirada, Ca 90638
Phone: (562) 404-4474 \* Fax: (562) 404-1773
ssdi@ssdi-power.com \* www.ssdi-power.com

1N7066 thru 1N7068
and
1N7066SMS thru 1N7068SMS

10 AMP
50 – 150 VOLTS
30 ns HYPERFAST RECOVERY
RECTIFIER

Designer's Data Sheet

Part Number/Ordering Information 1/

1N70

Screening 2/

- = Not Screened
TX = TX Level
TXV = TXV
S = S Level

Package Type

- = Axial Leaded
SMS = Surface Mount Square Tab

Voltage/Family

- 66= 50V
67 = 100V
68 = 150V

FEATURES:

- Hyper Fast Reverse Recovery: 30ns Maximum 4/
High Surge Current: 325 A Maximum
Hermetically Sealed
Low Forward Voltage Drop .95 @10A
Void Free Chip Construction
Solid Silver Leads
Available in Axial & Square Tab Versions
TX, TXV, and S-Level Screening Available 2/
Axial Lead Higher Current Replacements for:
1N5807, 1N5809, 1N5811
Possible SMS Replacements for Stud Mount :
1N5812, 1N5814, 1N5816


MAXIMUM RATINGS 3/

Table with 4 columns: RATING, SYMBOL, VALUE, UNIT. Rows include Peak Repetitive Reverse Voltage, Average Rectified Forward Current, Peak Surge Current, Operating & Storage Temperature, and Thermal Resistance.


NOTES:

- 1/ For Ordering Information, Price, Operating Curves, and Availability- Contact Factory.
2/ Screening Based on MIL-PRF-19500. Screening Flows Available on Request.
3/ Unless Otherwise Specified, All Electrical Characteristics @25°C.
4/ IF = 1A, IR = 1A, IRR = 0.1A, TA = 25°C
5/ Operating at higher Io currents may be achieved based on specific application and device mounting if Tj is maintained below 175°C.

Axial Leaded



SMS



NOTE: All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0119C

DOC



**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638  
 Phone: (562) 404-4474 \* Fax: (562) 404-1773  
 ssdi@ssdi-power.com \* www.ssdi-power.com

**1N7066 thru 1N7068  
 and  
 1N7066SMS thru 1N7068SMS**

<b>ELECTRICAL CHARACTERISTICS <sup>3/</sup></b>				
CHARACTERISTICS	SYMBOL	VALUE	UNIT	
		<b>MAX</b>		
Instantaneous Forward Voltage Drop	$I_F = 6.0 \text{ Adc}, T_A = +25^\circ\text{C}, 300\mu\text{s pulse}$	$V_{F1}$	0.900	Vdc
	$I_F = 10 \text{ Adc}, T_A = 25^\circ\text{C}, 300\mu\text{s pulse}$	$V_{F2}$	0.950	
	$I_F = 20 \text{ Adc}, T_A = 25^\circ\text{C}$	$V_{F3}$	1.020	
	$I_F = 6 \text{ Adc}, T_A = 125^\circ\text{C}$	$V_{F4}$	0.85	
	$I_F = 6 \text{ Adc}, T_A = -55^\circ\text{C}$	$V_{F5}$	1.05	
Reverse Leakage Current	Rated $V_R, T_A = +25^\circ\text{C}, 300\mu\text{s pulse minimum}$	$I_{R1}$	20	$\mu\text{A}$
	Rated $V_R, T_A = +100^\circ\text{C}, 300\mu\text{s pulse minimum}$	$I_{R2}$	1	mA
Junction Capacitance $V_R = 10 \text{ Vdc}, f = 1\text{MHz}, T_A = 25^\circ\text{C}$		$C_J$	80	pF
Reverse Recovery Time $I_F = 1\text{A}, I_R = 1\text{A}, I_{RR} = 0.1\text{A}, T_A = 25^\circ\text{C}$		$t_{rr}$	30	ns

**Package Outlines:**

DIMENSIONS (inches)			DIMENSIONS (inches)		
DIM.	Minimum	Maximum	DIM.	Minimum	Maximum
A	.135	.165	A	.172	.180
B	.135	.155	B	.180	.220
C	.037	.042	C	.020	.028
D	1.000	---	D	.002	---

<p><b>AXIAL</b></p>	<p><b>SMS</b></p>
---------------------	-------------------

**NOTE:** All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RC0119C**

**DOC**