

Electrical Characteristics

Part Number	Impedance (±25%)	Test Frequency (MHz) 200mV	DC Resistance () Max	Rated current (mA) Max
SBJ 201209T-070Y-N	7	100	0.10	600
SBJ 201209T-110Y-N	11	100	0.10	600
SBJ 201209T-170Y-N	17	100	0.10	600
SBJ 201209T-190Y-N	19	100	0.10	600
SBJ 201209T-260Y-N	26	100	0.10	600
SBJ 201209T-320Y-N	32	100	0.10	600
SBJ 201209T-400Y-N	40	100	0.10	500
SBJ 201209T-500Y-N	50	100	0.10	500
SBJ 201209T-600Y-N	60	100	0.15	500
SBJ 201209T-700Y-N	70	100	0.15	500
SBJ 201209T-800Y-N	80	100	0.15	500
SBJ 201209T-121Y-N	120	100	0.25	300
SBJ 201209T-221Y-N	220	100	0.30	300
SBJ 201209T-301Y-N	300	100	0.30	300
SBJ 201209T-471Y-N	470	100	0.40	300
SBJ 201209T-601Y-N	600	100	0.40	300
SBJ 201209T-751Y-N	750	100	0.50	200
SBJ 201209T-102Y-N	1000	100	0.50	200
SBJ 201209T-152Y-N	1500	100	0.60	200
SBJ 201209T-202Y-N	2000	100	0.70	200
SBJ 201209T-222Y-N	2200	100	0.80	200
SBJ 201209T-252Y-N	2500	100	0.80	200

Test Instruments : HP4291A Impedance / Material Analyzer



