

Electrical Characteristics

Part Number	Impedance (±25%)	Test Frequency (MHz) 200mV	DC Resistance () Max	Rated current (mA) Max
SBJ 160808T-070Y-N	7	100	0.05	500
SBJ 160808T-110Y-N	11	100	0.05	500
SBJ 160808T-190Y-N	19	100	0.08	500
SBJ 160808T-260Y-N	26	100	0.10	400
SBJ 160808T-320Y-N	32	100	0.10	400
SBJ 160808T-500Y-N	50	100	0.10	400
SBJ 160808T-600Y-N	60	100	0.10	400
SBJ 160808T-700Y-N	70	100	0.15	400
SBJ 160808T-800Y-N	80	100	0.15	400
SBJ 160808T-121Y-N	120	100	0.25	400
SBJ 160808T-221Y-N	220	100	0.30	400
SBJ 160808T-301Y-N	300	100	0.40	400
SBJ 160808T-471Y-N	470	100	0.40	400
SBJ 160808T-601Y-N	600	100	0.40	400
SBJ 160808T-751Y-N	750	100	0.60	300
SBJ 160808T-102Y-N	1000	100	0.60	300
SBJ 160808T-152Y-N	1500	100	0.80	200
SBJ 160808T-202Y-N	2000	100	1.0	200
SBJ 160808T-222Y-N	2200	100	1.0	200
SBJ 160808T-252Y-N	2500	100	1.0	200

Test Instruments : HP4291A Impedance / Material Analyzer





