

MP4411

High Power, High Speed Switching Applications
 For Printer Head Pin Driver and Pulse Motor Driver
 For Solenoid Driver

- 4-V gate drivability
- Small package by full molding (SIP 12 pin)
- High drain power dissipation (4-device operation)
 : P_T = 28 W (T_c = 25°C)
- Low drain-source ON resistance: R_{DS (ON)} = 0.28 Ω (typ.)
- High forward transfer admittance: |Y_{fs}| = 3.5 S (typ.)
- Low leakage current: I_{GSS} = ±10 μA (max) (V_{GS} = ±16 V)
 I_{DSS} = 100 μA (max) (V_{DS} = 100 V)
- Enhancement-mode: V_{th} = 0.8 to 2.0 V (V_{DS} = 10 V, I_D = 1 mA)

Absolute Maximum Ratings (Ta = 25°C)

| Characteristics | | Symbol | Rating | Unit |
|--|---------------------|------------------|------------|------|
| Drain-source voltage | | V _{DSS} | 100 | V |
| Drain-gate voltage (R _{GS} = 20 kΩ) | | V _{DGR} | 100 | V |
| Gate-source voltage | | V _{GS} | ±20 | V |
| Drain current | DC | I _D | 3 | A |
| | Pulse | I _{DP} | 12 | |
| Drain power dissipation (1-device operation, Ta = 25°C) | | P _D | 2.2 | W |
| Drain power dissipation (4-device operation) | Ta = 25°C | P _{DT} | 4.4 | W |
| | Tc = 25°C | | 28 | |
| Single pulse avalanche energy (Note 1) | | E _{AS} | 140 | mJ |
| Avalanche current | | I _{AR} | 3 | A |
| Repetitive avalanche energy (Note 2) | 1 device operation | E _{AR} | 0.22 | mJ |
| | 4 devices operation | E _{ART} | 0.44 | |
| Channel temperature | | T _{ch} | 150 | °C |
| Storage temperature range | | T _{stg} | -55 to 150 | °C |

Note 1: Condition for avalanche energy (single pulse) measurement

$$V_{DD} = 50 \text{ V, starting } T_{ch} = 25^\circ\text{C, } L = 20 \text{ mH, } R_G = 25 \text{ } \Omega, I_{AR} = 3 \text{ A}$$

Note 2: Repetitive rating; pulse width limited by maximum channel temperature


Note 3: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/Derating Concept and Methods) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

This transistor is an electrostatic-sensitive device. Please handle with caution.


Industrial Applications

Unit: mm



Weight: 3.9 g (typ.)

Array Configuration



Thermal Characteristics

| Characteristics | Symbol | Max | Unit |
|---|------------------------|------|--------------------|
| Thermal resistance from channel to ambient (4-device operation, $T_a = 25^\circ\text{C}$) | $\Sigma R_{th} (ch-a)$ | 28.4 | $^\circ\text{C/W}$ |
| Thermal resistance from channel to case (4-device operation, $T_c = 25^\circ\text{C}$) | $\Sigma R_{th} (ch-c)$ | 4.46 | $^\circ\text{C/W}$ |
| Maximum lead temperature for soldering purposes (3.2 mm from case for $t = 10$ s) | T_L | 260 | $^\circ\text{C}$ |

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

| Characteristics | | Symbol | Test Condition | Min | Typ. | Max | Unit |
|--|---------------|---------------|---|-----|------|----------|---------------|
| Gate leakage current | | I_{GSS} | $V_{GS} = \pm 16$ V, $V_{DS} = 0$ V | — | — | ± 10 | μA |
| Drain cut-off current | | I_{DSS} | $V_{DS} = 100$ V, $V_{GS} = 0$ V | — | — | 100 | μA |
| Drain-source breakdown voltage | | $V_{(BR)DSS}$ | $I_D = 10$ mA, $V_{GS} = 0$ V | 100 | — | — | V |
| Gate threshold voltage | | V_{th} | $V_{DS} = 10$ V, $I_D = 1$ mA | 0.8 | — | 2.0 | V |
| Drain-source ON resistance | | $R_{DS(ON)}$ | $V_{GS} = 4$ V, $I_D = 2$ A | — | 0.36 | 0.45 | Ω |
| | | | $V_{GS} = 10$ V, $I_D = 2$ A | — | 0.28 | 0.35 | |
| Forward transfer admittance | | $ Y_{fs} $ | $V_{DS} = 10$ V, $I_D = 2$ A | 1.5 | 3.5 | — | S |
| Input capacitance | | C_{iss} | $V_{DS} = 10$ V, $V_{GS} = 0$ V, $f = 1$ MHz | — | 280 | — | μF |
| Reverse transfer capacitance | | C_{rss} | | — | 50 | — | μF |
| Output capacitance | | C_{oss} | | — | 105 | — | μF |
| Switching time | Rise time | t_r | | — | 20 | — | ns |
| | Turn-on time | t_{on} | | — | 50 | — | |
| | Fall time | t_f | | — | 40 | — | |
| | Turn-off time | t_{off} | | — | 170 | — | |
| Total gate charge (gate-source plus gate-drain) | | Q_g | $V_{DD} \approx 80$ V, $V_{GS} = 10$ V, $I_D = 3$ A | — | 13.5 | — | nC |
| Gate-source charge | | Q_{gs} | | — | 8.5 | — | nC |
| Gate-drain ("miller") charge | | Q_{gd} | | — | 5 | — | nC |


Source-Drain Diode Ratings and Characteristics (Ta = 25°C)







| Characteristics | Symbol | Test Condition | Min | Typ. | Max | Unit |
|----------------------------------|-----------|--|-----|------|------|------|
| Continuous drain reverse current | I_{DR} | — | — | — | 3 | A |
| Pulse drain reverse current | I_{DRP} | — | — | — | 12 | A |
| Diode forward voltage | V_{DSF} | IDR = 3 A, VGS = 0 V | — | — | -1.5 | V |
| Reverse recovery time | t_{rr} | IDR = 3 A, VGS = 0 V, dIDR/dt = 50 A/μs | — | 100 | — | ns |
| Reverse recovery charge | Q_{rr} | | — | 0.2 | — | μC |







Flyback-Diode Rating and Characteristics (Ta = 25°C)






| Characteristics | Symbol | Test Condition | Min | Typ. | Max | Unit |
|-----------------|----------|----------------|-----|------|-----|------|
| Forward current | I_{FM} | — | — | — | 3 | A |
| Reverse current | I_R | VR = 100 V | — | — | 0.4 | μA |
| Reverse voltage | V_R | IR = 100 μA | 100 | — | — | V |
| Forward voltage | V_F | IF = 0.5 A | — | — | 1.8 | V |

Marking









RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.