

## Point Source LED

Features:

- High Reliability in Demanding Environments
- Emitting Window Diameter  $\Phi$  50 $\mu$ m

Applications:

- Optical Switches
- Edge Sensing



## Absolute Maximum Ratings (Ta=25°C)

Items	Symbol	Ratings	Unit
Forward Current (DC)	IF	50	mA
Forward Current (Pulse)*1	IFP	200	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	100	mW
Operating Temperature	ToPr	-20 ~ +85	°C
Storage Temperature	Tstg	-30 ~ +100	°C

\*1: Tw ≤ 100 $\mu$  sec, (4% Duty)

## Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Conditions	Min	Typ	Max	Unit
Power Output	PO	IF=20mA	2.0	3.0	--	mW
Power Output*1	PO	IFP=200mA	(8.0)	--	--	mW
Forward Voltage	VF	IF=20mA	--	1.85	2.2	V
Reverse Current	IR	VR=5V	--	--	10	$\mu$ A
Peak Wavelength	$\lambda_p$	IF=20mA	--	850	--	nm
Spectral Line Half Width	$\Delta\lambda$	IF=20mA	--	40	--	nm
Half Intensity Beam Angle	$\theta$	IF=20mA	--	$\pm 50$	--	deg.

\*1: Tw ≤ 100 $\mu$  Sec, (4% Duty)

