

# YG861S12R (5A)

(120V / 5A )


[0401]

## High Voltage Schottky barrier diode

### ■ Major characteristics


Characteristics	YG861S12R	Units	Condition
V <sub>RRM</sub>	120	V	
V <sub>F</sub>	0.88	V	T <sub>c</sub> =25°C MAX.
I <sub>o</sub>	5	A	

### ■ Outline drawings, mm



Package : TO-220F  
Epoxy resin UL : V-0

### ■ Connection diagram



### ■ Maximum ratings and characteristics

- Absolute maximum ratings (at T<sub>c</sub>=25°C Unless otherwise specified )

Item	Symbol	Conditions	Rating	Unit
Repetitive peak surge reverse voltage	V <sub>RSM</sub>	t <sub>w</sub> =500ns, duty=1/40	120	V
Repetitive peak reverse voltage	V <sub>RRM</sub>		120	V
Isolating voltage	V <sub>iso</sub>	Terminals-to-Case, AC,1min	1500	V
Average output current	I <sub>o</sub>	Square wave, duty=1/2 T <sub>c</sub> =104°C	5	A
Non-repetitive surge current	I <sub>FSM</sub>	Sine wave 10ms 1shot	75	A
Operating junction temperature	T <sub>j</sub>		+150	°C
Storage temperature	T <sub>stg</sub>		-40 to +150	°C

- Electrical characteristics (at T<sub>c</sub>=25°C Unless otherwise specified )

Item	Symbol	Conditions	Max.	Unit
Forward voltage drop	V <sub>F</sub>	I <sub>FM</sub> =10A	0.88	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> =V <sub>RRM</sub>	150	µA
Thermal resistance	R <sub>th(j-c)</sub>	Junction to case	5.0	°C/W

- Mechanical characteristics

Mounting torque	Recommended torque	0.3 to 0.5	N·m
Approximate mass		2	g

## ■ Characteristics

