


- Features :
- Economical open frame design
- Wide input range
- High efficiency up to 96%
- Built-in remote ON / OFF control
- Compact size 2.0"x1.024"x 0.421"(SIP package)
- Cooling by free air convection
- Protections: Short circuit / Overload / Over voltage
- 100% burn-in test
- Low cost / High reliability
- 2 years warranty

**SPECIFICATION**

ORDER NO.	NID60S24-05	NID60S24-12	NID60S24-15	NID60S48-24		
OUTPUT	DC VOLTAGE	5V	12V	15V	24V	
	CURRENT RANGE	0 ~ 4A	0 ~ 4A	0 ~ 4A	0 ~ 2.5A	
	RATED POWER	20W	48W	60W	60W	
	RIPPLE & NOISE (max.) Note.2	100mVp-p	120mVp-p	150mVp-p	200mVp-p	
	LINE REGULATION Note.3	±0.5%				
	LOAD REGULATION Note.4	±0.5%				
	VOLTAGE ACCURACY	±2.0%				
	SWITCHING FREQUENCY (Typ.)	250KHz				
INPUT	EXTERNAL CAPACITANCE LOAD (max.)	100uF / 25V low ESR	68uf/16V low ESR	47uf/50V low ESR		
	VOLTAGE RANGE	20 ~ 53VDC	20 ~ 53VDC	20 ~ 53VDC	30 ~ 53VDC	
	NORMAL VOLTAGE	24VDC (or 48VDC)	24VDC (or 48VDC)	24VDC (or 48VDC)	48VDC	
	EFFICIENCY (Typ.)	90%	95%	96%	95%	
	DC CURRENT	Full load	940mA	2120mA	2610mA	1320mA
		No load	20mA	30mA	30mA	50mA
PROTECTION	Fuse recommended (5A)					
PROTECTION	OVERLOAD (Typ.)	120 ~ 300% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed				
	SHORT CIRCUIT	All output equipped with short circuit Protection type : Hiccup mode, recovers automatically after fault condition is removed				
	OVER VOLTAGE	Protection type : Shut off o/p voltage, clamp by TVS diode				
ENVIRONMENT	WORKING TEMP.	-25 ~ +65°C (Refer to output load derating curve)				
	WORKING HUMIDITY	20% ~ 85% RH non-condensing				
	STORAGE TEMP., HUMIDITY	-25 ~ +105°C, 10 ~ 85% RH				
	TEMP. COEFFICIENT	±0.03% / °C (0 ~ 50°C)				
OTHERS	VIBRATION	10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes				
	REMOTE CONTROL	Power on : 3.3VDC < R.C ~ com < 12VDC or open circuit ; power off : R.C ~ com < 0.4VDC or short circuit (PIN5,6 & PIN11)				
	DIMENSION	50.8*26*10.7mm or 2.0**1.024**0.421" inch (L*W*H)				
	WEIGHT	15g				


■ Mechanical Specification



■ Pin Configuration

Pin No.	Output
1, 2, 3, 4	+Vout
5, 6	Com
7, 8	+Vin
9, 10	N.C.
11	R.C.

■ Derating Curve



NOTE

- 1.All parameters are specified at normal input, rated load, 25°C 70% RH Ambient.
- 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
- 3.Line regulation is measured from low line to high line at rated load.
- 4.Load regulation is measured from 10% to 100% rated load.