

500VA Inverter with Sine Wave Output Rugged, Industrial Quality CSI 500-FT Series



- Rugged, field-proven design
- Sinusoidal output voltage
- Filtered input
- Full electronic protection
- Conduction/convection cooling

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate 500VA output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. The use of high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. Cooling is via baseplate to a heatsinking surface and by natural convection. The use of components with established reliability results in high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 36V, 48V, 125V, 250Vdc
+/-15% are standard
Consult factory for other inputs

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

Compliant to input and output voltages according to the corresponding standards

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950

EMI

EN 55022 Class A
as a minimum

Output Voltage

115Vac/4.34A/60Hz or 400Hz;
or 230Vac/2.17A/50Hz
Output neutral is connected to the chassis internally.
Isolated floating output optional
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

Maximum $\pm 6\%$ from no load to full load.
 $\pm 2\%$ load regulation option is available

Load Crest Factor

Maximum 3.0 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection.

Output Overvoltage Protection

Output voltage is limited by internal supply voltage

Efficiency

Input voltage dependent
Typically 80% at full load

Operating Temperature Range

0° C to +50° C for full specification without derating.
Extended temperature ranges available

Temperature Drift

0.05% per °C over operating temperature range

Cooling

Conduction to customer heatsink or chassis and natural convection

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal coating as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

120,000 hours at 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None
Remote shutdown as option

Alarm Output

Optional output fail alarm (Form C)

Dimensions (W x H x L)

F21: 254 x 66 x 361 mm
(10" x 2.6" x 14.2") including terminal block and flanges

Weight

4.2 kg (9 lb)

Connections

Input/output: Compression-type terminals

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request. Specifications are subject to change

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com