

Long-life grade capacitors

Applications


- General industrial electronics
- For switch-mode power supplies in professional equipment

Features

- High reliability
- High ripple current capability
- All-welded construction ensures reliable electrical contact
- Version with low-inductance design available

Construction


- Charge-discharge proof, polar
- Aluminum case with insulating sleeve
- Poles with screw terminal connections
- Mounting with ring clips, clamps or threaded stud
- The bases of types with threaded stud are not insulated



B43456

KAL0567-B

B43458



Specifications and characteristics in brief

Rated voltage U_R	16 ... 100 VDC	
Surge voltage U_S	$1,15 \cdot U_R$	
Rated capacitance C_R	2 200 ... 680 000 μF	
Capacitance tolerance	$\pm 20 \% \triangleq \text{M}$	
Leakage current I_L (5 min, 20 °C)	$I_L \leq 0,3 \mu\text{A} \cdot \left(\frac{C_R}{\mu\text{F}} \cdot \frac{U_R}{\text{V}} \right)^{0,7} + 4 \mu\text{A}$	
Self-inductance ESL	Approx. 20 nH Capacitors with low-inductance design: $d \geq 64,3 \text{ mm}$: approx. 13 nH	
Useful life 85 °C; U_R ; $I_{\sim R}$ 40 °C; U_R ; $2,9 \cdot I_{\sim R}$	> 12 000 h > 200 000 h	Requirements: $\Delta C/C \leq \pm 45 \%$ of initial value $ESR \leq 3$ times initial specified limit $I_L \leq$ initial specified limit Failure percentage: $\leq 1 \%$ Failure rate: $\leq 40 \text{ fit} (\leq 40 \cdot 10^{-9}/\text{h})$ (for definiton "fit", refer to chapter "Quality", page 62)
Voltage endurance test 85 °C; U_R	2 000 h	Post test requirements: $\Delta C/C \leq \pm 15 \%$ of initial value $ESR \leq 1,3$ times initial specified limit $I_L \leq$ initial specified limit
Vibration resistance	To IEC 60068-2-6, test Fc: displacement amplitude 0,75 mm, frequency range 10 to 55 Hz, acceleration max. 10 g, duration $3 \times 2 \text{ h}$	
IEC climatic category	To IEC 60068-1: 40/085/56 (– 40 °C/+ 85 °C/56 days damp heat test)	
Detail specification	Similar to CECC 30301-810	
Sectional specification	IEC 60384-4	

Ripple current capability


Due to the ripple current capability of the contact elements, the following current upper limits must not be exceeded:

Capacitor diameter	$\leq 51,6 \text{ mm}$	64,3 mm	76,9 mm
$I_{\sim \text{max}}$	30 A	40 A	50 A




Dimensional drawings

Type B41456
Ring clip/clamp mounting



M5: min. reach of screw = 8 mm
M6: min. reach of screw = 12 mm*)
) 8 mm for low-inductance design

Type B41458
Threaded stud mounting



Positive pole marking: +

Screw terminals with UNF threads are available upon request.

Dimensions and weights


Ter- minal	Dimensions (mm) with insulating sleeve										Approx. wt. (g)
	d	$l \pm 1$	$l_1 \pm 1$	$l_2 \begin{smallmatrix} +0 \\ -1 \end{smallmatrix}$	l_3	d_1	$d_2 \text{ max}$	$d_3 \text{ max}$	$a \begin{smallmatrix} +0,2 \\ -0,4 \end{smallmatrix}$		
M 5	35,7+ 0/- 0,8	55,7	62,2	13	7,0+ 0,2/- 1	M 8	8,2	13,5	12,7	65	
M 5	35,7+ 0/- 0,8	80,7	87,2	13	7,0+ 0,2/- 1	M 8	8,2	13,5	12,7	105	
M 5	35,7+ 0/- 0,8	105,7	112,2	13	7,0+ 0,2/- 1	M 8	8,2	13,5	12,7	135	
M 5	51,6+ 0/- 0,8	80,7	87,2	17	7,0+ 0,2/- 1	M 12	8,2	13,5	22,2	220	
M 5	51,6+ 0/- 0,8	105,7	112,2	17	7,0+ 0,2/- 1	M 12	8,2	13,5	22,2	280	
M 5	64,3+ 0/- 0,8	105,7	112,2	17	7,0+ 0,2/- 1	M 12	8,2	13,5	28,5	440	
M 6	76,9+ 0/- 0,7	105,7	111,5	17	6,4+ 1,1/- 0,8	M 12	17,7	17,7	31,7	540	
M 6	76,9+ 0/- 0,7	143,2	149,0	17	6,4+ 1,1/- 0,8	M 12	17,7	17,7	31,7	840	
M 6	76,9+ 0/- 0,7	220,7	226,5	17	6,4+ 1,1/- 0,8	M 12	17,7	17,7	31,7	1300	

Dimensions are also valid for low-inductance design.

Packing

For ecological reasons the packing is pure cardboard.

Capacitor diameter d	Packing units (pieces)
35,7 mm	36
51,6 mm	22
64,3 mm	15
76,9 mm	12



B41456 / B41458

Compact – 85 °C

Special designs

- Low-inductance design

Ordering code:

Design	Identification in 3rd block of ordering code	Remark
Low inductance (13 nH)	M003	For capacitors with diameter $d \geq 64,3$ mm

Accessories

The following items are included in the delivery package, but are not fastened to the capacitors:

	Thread	Toothed washers	Screws/Nuts	Maximum torque
For terminals	M 5	A 5,1 DIN 6797	Cylinder-head screw M 5 × 8 DIN 84-4.8	2 Nm
	M 6	A 6,4 DIN 6797	Cylinder-head screw M 6 × 12 DIN 85-4.8	2,5 Nm
For mounting	M 8	J 8,2 DIN 6797	Hex nut BM 8 DIN 439	4 Nm
	M 12	J 12,5 DIN 6797	Hex nut BM 12 DIN 439	10 Nm

The following must be ordered separately:

Ring clips


B44030 (cf. page 169)

Clamps for capacitors with $d \geq 64,3$ mm

B44030 (cf. page 173)


Insulating parts

B44020 (cf. page 166)


Overview of available types

U_R (VDC)	16	25	40	63	100
C_R (μ F)	Case dimensions $d \times l$ (mm)				
2 200					35,7 × 55,7
3 300					35,7 × 80,7
4 700				35,7 × 55,7	35,7 × 80,7
6 800				35,7 × 55,7	35,7 × 105,7
10 000			35,7 × 55,7	35,7 × 80,7	51,6 × 80,7
15 000			35,7 × 80,7	35,7 × 105,7	51,6 × 105,7
22 000	35,7 × 55,7	35,7 × 55,7	35,7 × 80,7	51,6 × 80,7	64,3 × 105,7
33 000	35,7 × 55,7	35,7 × 80,7	35,7 × 105,7	51,6 × 105,7	76,9 × 105,7
47 000	35,7 × 80,7	35,7 × 105,7	51,6 × 80,7	64,3 × 105,7	76,9 × 143,2
68 000	35,7 × 105,7	51,6 × 80,7	51,6 × 105,7	76,9 × 105,7	
100 000	51,6 × 80,7	51,6 × 105,7	64,3 × 105,7	76,9 × 143,2	
150 000	51,6 × 80,7	64,3 × 105,7	76,9 × 105,7	76,9 × 220,7	
220 000	64,3 × 105,7	64,3 × 105,7	76,9 × 143,2		
330 000	64,3 × 105,7	76,9 × 143,2			
470 000	76,9 × 143,2	76,9 × 220,7			
680 000	76,9 × 143,2				


The capacitance and voltage ratings listed above are available in different cases upon request.
Other voltage and capacitance ratings are also available upon request.


Technical data and ordering codes

U_R VDC	C_R 100 Hz 20 °C μF	Case dimensions $d \times l$ mm	ESR_{max} 100 Hz 20 °C m Ω	Z_{max} 10 kHz 20 °C m Ω	$I_{\sim\text{max}}$ 100 Hz 40 °C A	$I_{\sim R}$ 100 Hz 85 °C A	Ordering code ¹⁾
16	22 000	35,7 × 55,7	28	23	21	7,1	B4145*B4229M000
	33 000	35,7 × 55,7	21	17	24	8,3	B4145*B4339M000
	47 000	35,7 × 80,7	16	13	30	11	B4145*B4479M000
	68 000	35,7 × 105,7	13	10	30	13	B4145*B4689M000
	100 000	51,6 × 80,7	10	8,2	30	14	B4145*B4100M000
	150 000	51,6 × 80,7	8,4	6,8	30	15	B4145*B4150M000
	220 000	64,3 × 105,7	7,3	5,9	40	20	B4145*B4220M000 ²⁾
	330 000	64,3 × 105,7	6,6	5,3	40	21	B4145*B4330M000 ²⁾
	470 000	76,9 × 143,2	6,1	4,9	50	25	B4145*B4470M000 ²⁾
680 000	76,9 × 143,2	5,8	4,6	50	26	B4145*B4680M000 ²⁾	
25	22 000	35,7 × 55,7	25	20	22	7,7	B4145*B5229M000
	33 000	35,7 × 80,7	19	15	29	10	B4145*B5339M000
	47 000	35,7 × 105,7	15	12	30	12	B4145*B5479M000
	68 000	51,6 × 80,7	12	9,3	30	13	B4145*B5689M000
	100 000	51,6 × 105,7	9,5	7,6	30	16	B4145*B5100M000
	150 000	64,3 × 105,7	8,0	6,4	40	20	B4145*B5150M000 ²⁾
	220 000	64,3 × 105,7	7,0	5,6	40	21	B4145*B5220M000 ²⁾
	330 000	76,9 × 143,2	6,4	5,1	50	25	B4145*B5330M000 ²⁾
470 000	76,9 × 220,7	6,0	4,8	50	31	B4145*B5470M000 ²⁾	
40	10 000	35,7 × 55,7	37	34	18	6,3	B4145*B7109M000
	15 000	35,7 × 80,7	27	24	24	8,3	B4145*B7159M000
	22 000	35,7 × 80,7	20	18	28	9,6	B4145*B7229M000
	33 000	35,7 × 105,7	15	13	30	12	B4145*B7339M000
	47 000	51,6 × 80,7	12	10	30	13	B4145*B7479M000
	68 000	51,6 × 105,7	10	8,4	30	16	B4145*B7689M000
	100 000	64,3 × 105,7	8,2	7,0	40	19	B4145*B7100M000 ²⁾
	150 000	76,9 × 105,7	7,2	6,0	50	21	B4145*B7150M000 ²⁾
220 000	76,9 × 143,2	6,5	5,4	50	25	B4145*B7220M000 ²⁾	

Preferred types


- 1) * "6" = for capacitors with ring clip/clamp mounting
 "8" = for capacitors with threaded stud
 2) For low-inductance design, see page 76.


Technical data and ordering codes

U_R VDC	C_R 100 Hz 20 °C μF	Case dimensions $d \times l$ mm	ESR_{max} 100 Hz 20 °C m Ω	Z_{max} 10 kHz 20 °C m Ω	$I_{\sim\text{max}}$ 100 Hz 40 °C A	$I_{\sim R}$ 100 Hz 85 °C A	Ordering code ¹⁾
63	4 700	35,7 × 55,7	60	58	14	4,9	B4145*B8478M000
	6 800	35,7 × 55,7	43	42	17	5,9	B4145*B8688M000
	10 000	35,7 × 80,7	31	30	23	7,7	B4145*B8109M000
	15 000	35,7 × 105,7	22	21	30	10	B4145*B8159M000
	22 000	51,6 × 80,7	16	16	30	11	B4145*B8229M000
	33 000	51,6 × 105,7	12	12	30	14	B4145*B8339M000
	47 000	64,3 × 105,7	10	9,4	40	18	B4145*B8479M000 ²⁾
	68 000	76,9 × 105,7	7,9	7,8	50	20	B4145*B8689M000 ²⁾
	100 000	76,9 × 143,2	6,7	6,6	50	25	B4145*B8100M000 ²⁾
	150 000	76,9 × 220,7	5,8	5,7	50	31	B4145*B8150M000 ²⁾
100	2 200	35,7 × 55,7	80	70	13	4,3	B4145*B9228M000
	3 300	35,7 × 80,7	55	48	17	5,8	B4145*B9338M000
	4 700	35,7 × 80,7	40	35	20	6,7	B4145*B9478M000
	6 800	35,7 × 105,7	29	25	25	8,7	B4145*B9688M000
	10 000	51,6 × 80,7	22	18	30	10	B4145*B9109M000
	15 000	51,6 × 105,7	16	14	30	13	B4145*B9159M000
	22 000	64,3 × 105,7	13	11	40	17	B4145*B9229M000 ²⁾
	33 000	76,9 × 105,7	10	8,4	50	19	B4145*B9339M000 ²⁾
	47 000	76,9 × 143,2	8,5	7,1	50	24	B4145*B9479M000 ²⁾

Preferred types

- 1) * "6" = for capacitors with ring clip/clamp mounting
"8" = for capacitors with threaded stud
- 2) For low-inductance design, see page 76.




B41456 / B41458


Compact – 85 °C

Useful life

depending on ambient temperature T_A under ripple current operating conditions¹⁾




Frequency factor of permissible ripple current I_{\sim} versus frequency f




d (mm)	35,7	51,6	64,3	76,9
≤ 63 VDC	a	a	a	b
100 VDC	c	d	d	e

1) Refer to page 40 for an explanation on how to interpret the useful life graphs.




Frequency characteristics of ESR
Typical behavior



<i>d</i> (mm)	35,7	51,6	64,3	76,9
≤ 63 VDC	a	a	a	b
100 VDC	c	d	d	e

Impedance Z
versus frequency *f*
Typical behavior at 20 °C



Herausgegeben von EPCOS AG

Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.