

5 Energy Way, P.O. Box 1019, West Warwick, RI 02893 USA Tel. 800-424-9850/401-823-5200 • Fax 401-823-8723 • Email info@advintcorp.com • Internet http://www.advintcorp.com

# .050" (1.27mm) Pitch Board to Board Interconnections



### Features:

- Sockets and adapters are designed in mating pairs.
- .050" (1.27mm) and .100" (2.54mm) centers spacing row to row.
- High reliability screw machine terminals with closed end construction for 100% antiwicking of solder.
- For surface mount board to board options consult factory.

### **Terminals and Contacts:**

Terminal: Brass - Copper Alloy (C36000), ASTM-B-16 Contact: Beryllium Copper - Copper Alloy (C17200), ASTM-B-194

### **Plating:**

Terminal: Gold over Nickel or Tin-Lead over Nickel Contact: Gold over Nickel or Tin-Lead over Nickel


### **Body Material:**

**Molded -** Glass Filled Thermoplastic Polyester (P.B.T.), U.L. Rated 94V-O, -60°C to 140°C (-76°F to 284°F)


**High Temp. Molded** - High temp. glass filled thermoplastic, U.L. Rated 94V-O, -60°C to 260°C (-76°F to 500°F)


**Peel-A-Way**<sup>®</sup> - Polyimide Film, Temp. range -269°C to 400°C (-452°F to 752°F)

### How To Order - Male




Body Type \_\_\_\_\_\_ KBA - Single Row Peel-A-Way<sup>®</sup> KNA - Dual Row Peel-A-Way<sup>®</sup> \*KDA - Dual Row Peel-A-Way<sup>®</sup> (.100/(2.54) Pitch Between Rows)






**Single Row** 




### Molded

# of Pins Per Row	X	Y	
10	.550 (13.97)	.450 (11.43) .950 (24.13)	
20	1.050 (26.67)		
30	1.550 (39.37)	1.450 (36.83)	
40	2.050 (52.07)	1.950 (49.53)	
50	2.550 (64.77)	2.450 (62.23)	






Dual Row .050" (1.27mm) Spacing Row to Row KNA, DDA - Male / DDS, KNS - Female




Dual Row .100" (2.54mm) Spacing Row to Row DAD, KDA - Male / DD, KDD - Female P/N Ex. KDA020-131T



### **Peel-A-Way®**

# of Pins Per Row	x	Y	
10	.650 (16.51)	.450 (11.43)	
20	1.150 (29.21)	.950 (24.13)	
30	1.650 (41.91)	1.450 (36.83)	
40	2.150 (54.61)	1.950 (49.53)	0
50	2.650 (67.31)	2.450 (62.23)	

Multiply number of rows times number of pins per row for total pin count to order.




Peel-A-Way® covered by patent rights issued and/or pending

Products shown covered by patents issued and/or pending. Specifications subject to change without notice.



5 Energy Way, P.O. Box 1019, West Warwick, RI 02893 USA Tel. 800-424-9850/401-823-5200 • Fax 401-823-8723 • Email info@advintcorp.com • Internet http://www.advintcorp.com

## .050" (1.27mm) Pitch Board to Board Interconnections



U Quick turn delivery available on standard terminal types.

Additional terminal types available. See terminal section for detailed terminal information.


Peel-A-Way<sup>®</sup> covered by patent rights issued and/or pending.




5 Energy Way, P.O. Box 1019, West Warwick, RI 02893 USA Tel. 800-424-9850/401-823-5200 • Fax 401-823-8723 • Email info@advintcorp.com • Internet http://www.advintcorp.com

## .050" (1.27mm) Pitch Board to Board Interconnections

### **Thru Hole Male & Female**



### **Thru Hole Male & Surface Mount Female**



Molded Male & Female

Order One Each Male & Female To Get the Required "A" Dim.

	Order One Each Male & Female 10 Get the Required A Dim.					
Fig. #	Female Part #	Male Part #	A	С	В	
3	KBS020-227TG	KBA020-131G	.046 (1.17)	.015 (.38)	.031 (.79)	
3	KBS020-227TG	KBA020-321G	.085 (2.16)	.015 (.38)	.070 (1.78)	
3	KBS020-227TG	KBA020-322G	.100 (2.54)	.015 (.38)	.085 (2.16)	
2	KBS020-227TG	NBA020-233G	.122 (3.09)	.015 (.38)	.107 (2.71)	
4	SDS020-557TG	KBA020-131G	.143 (3.63)	.112 (2.84)	.031 (.79)	
5	SDS020-551TG	KBA020-131G	.149 (3.79)	.118 (3.00)	.031 (.79)	
4	SDS020-557TG	KBA020-321G	.182 (4.62)	.112 (2.84)	.070 (1.78)	
5	SDS020-551TG	KBA020-321G	.188 (4.78)	.118 (3.00)	.070 (1.78)	
5	SDS020-553TG	KBA020-131G	.192 (4.88)	.161 (4.09)	.031 (.79)	
4	SDS020-168TG	KBA020-131G	.196 (4.98)	.165 (4.19)	.031 (.79)	
4	SDS020-557TG	KBA020-322G	.197 (5.00)	.112 (2.84)	.085 (2.16)	
5	SDS020-551TG	KBA020-322G	.203 (5.16)	.118 (3.00)	.085 (2.16)	
1	SDS020-557TG	SDA020-233G	.219 (5.55)	.112 (2.84)	.107 (2.71)	
6	SDS020-551TG	NBA020-233G	.225 (5.71)	.118 (3.00)	.107 (2.71)	
5	SDS020-553TG	KBA020-321G	.231 (5.87)	.161 (4.09)	.070 (1.78)	
4	SDS020-168TG	KBA020-321G	.235 (5.97)	.165 (4.19)	.070 (1.78)	
4	SDS020-168TG	KBA020-322G	.250 (6.35)	.165 (4.19)	.085 (2.16)	
5	SDS020-553TG	KBA020-322G	.246 (6.25)	.161 (4.09)	.085 (2.16)	
1	SDS020-168TG	NBA020-233G	.272 (6.91)	.165 (4.19)	.071 (2.71)	
4	SDS020-205TG	KBA020-131G	.309 (7.85)	.278 (7.06)	.031 (.79)	
4	SDS020-205TG	KBA020-321G	.348 (8.84)	.278 (7.06)	.070 (1.78)	
4	SDS020-205TG	KBA020-322G	.363 (9.22)	.278 (7.06)	.085 (2.16)	
1	SDS020-205TG	NBA020-233G	.385 (9.77)	.278 (7.06)	.107 (2.71)	

20 Position Single Row Part Numbers Shown For Additional Ordering Information See Page 114

If required "A" dimension is not shown, consult factory.

Peel-A-Way<sup>®</sup> covered by patent rights issued and/or pending.



5 Energy Way, P.O. Box 1019, West Warwick, RI 02893 USA Tel. 800-424-9850/401-823-5200 • Fax 401-823-8723 • Email info@advintcorp.com • Internet http://www.advintcorp.com

## .050" (1.27mm) Pitch Board to Board Interconnections

### Surface Mount Male & Thru Hole Female




Figure 7 Peel-A-Way<sup>®</sup> Male & Female




Figure 8 Peel-A-Way<sup>®</sup> Male & Molded Female

### **Surface Mount Male & Female**




Figure 9 Peel-A-Way<sup>®</sup> Male & Molded Female

1		
E		
-		

В	С	Α	Male Part #	Female Part #	Fig. #
.031 (.79)	.015 (.38)	.046 (1.17)	KBA020-525G	KBS020-227TG	7
.050 (1.27)	.015 (.38)	.065 (1.65)	KBA020-526G	KBS020-227TG	7
.050 (1.27)	.118 (3.00)	.168 (4.27)	KBA020-526G	SDS020-551TG	9
.031 (.79)	.161 (4.09)	.192 (4.88)	KBA020-525G	SDS020-553TG	9
.031 (.79)	.165 (4.19)	.196 (4.98)	KBA020-525G	SDS020-168TG	8
.050 (1.27)	.161 (4.09)	.211 (5.36)	KBA020-526G	SDS020-553TG	9
.050 (1.27)	.165 (4.19)	.215 (5.46)	KBA020-526G	SDS020-168TG	8
.031 (.79)	.278 (7.06)	.309 (7.85)	KBA020-525G	SDS020-205TG	8
.050 (1.27)	.278 (7.06)	.326 (8.33)	KBA020-526G	SDS020-205TG	8

#### Order One Each Male & Female To Get the Required "A" Dim.

20 Position Single Row Part Numbers Shown For Additional Ordering Information See Page 114

If required "A" dimension is not shown, consult factory.