

Linear Systems replaces discontinued Siliconix 2N4416

The LS4416 is a N-Channel high frequency JFET amplifier

The LS4416 N-channel JFET is designed to provide high-performance amplification at high frequencies.

The SOT-23 package provides ease of manufacturing, and a lower cost assembly option.

LS4416 Benefits:

- Wideband High Gain
- Very High System Sensitivity
- High Quality of Amplification
- High-Speed Switching Capability
- High Low-Level Signal Amplification

LS4416 Applications:

- High-Frequency Amplifier / Mixer
- Oscillator
- Sample-and-Hold
- Very Low Capacitance Switches

FEATURES

DIRECT REPLACEMENT FOR SILICONIX 2N4416

EXCEPTIONAL GAIN (400 MHz)	10dB (min)
VERY LOW NOISE FIGURE (400 MHz)	4dB (max)

VERY LOW DISTORTION
HIGH AC/DC SWITCH OFF-ISOLATION

ABSOLUTE MAXIMUM RATINGS
@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature	-65°C to +200°C
Operating Junction Temperature	-55°C to +135°C

Maximum Power Dissipation

Continuous Power Dissipation	300mW
------------------------------	-------

MAXIMUM CURRENT

Gate Current (Note 1)	10mA
-----------------------	------

MAXIMUM VOLTAGES

Gate to Drain or Gate to Source	-30V
---------------------------------	------

LS4416 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
BV_{GSS}	Gate to Source Breakdown Voltage	-30	--	--	V	$I_G = -1\mu A, V_{DS} = 0V$
$V_{GS(off)}$	Gate to Source Cutoff Voltage	--	--	-6	V	$V_{DS} = 15V, I_D = 1nA$
I_{DSS}	Gate to Source Saturation Current	5	--	15	mA	$V_{DS} = 15V, V_{GS} = 0V$
I_{GSS}	Gate Leakage Current	--	--	-1.0	nA	$V_{GS} = -15V, V_{DS} = 0V$
g_{fs}	Forward Transconductance	4500	--	7500	μS	$V_{DS} = 15V, V_{GS} = 0V, f = 1kHz$
g_{os}	Output Conductance	--	--	50	μS	$V_{DS} = 15V, V_{GS} = 0V, f = 1MHz$
C_{iss}	Input Capacitance ²	--	--	0.8	pF	
C_{rss}	Reverse Transfer Capacitance ²	--	--	4	pF	
C_{oss}	Output Capacitance ²	--	--	2	pF	
e_n	Equivalent Input Noise Voltage	--	6	--	nV/ \sqrt{Hz}	$V_{DS} = 10V, V_{GS} = 0V, f = 1kHz$

LS4416 HIGH FREQUENCY ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	100 Mhz		400 Mhz		UNITS	CONDITIONS
		MIN	MAX	MIN	MAX		
g_{iss}	Input Conductance	--	100	--	1000	μS	$V_{DS} = 15V, V_{GS} = 0V$
b_{iss}	Input Susceptance ²	--	2500	--	10000		
g_{oss}	Output Conductance	--	75	--	100		
b_{oss}	Output Susceptance ²	--	1000	--	4000		
G_{fs}	Forward Transconductance	--	--	4000	--		
G_{ps}	Power Gain ²	18	--	10	--	dB	$V_{DS} = 15V, I_D = 5mA$
NF	Noise Figure ²	--	2	--	4		$V_{DS} = 15V, I_D = 5mA, R_G = 1k\Omega$

- NOTES**
- Absolute maximum ratings are limiting values above which LS4416 serviceability may be impaired.
 - Not production tested, guaranteed by design

Micross Components Europe



Tel: +44 1603 788967

Email: chipcomponents@micross.com


Web: <http://www.micross.com/distribution>

Available Packages:

LS4416 in SOT-23

LS4416 in bare die.

SOT-23 (Top View)



Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.