

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

## Features

- Low Power Loss
- High Efficiency
- Low Forward Voltage , High Current Capability
- High surge capacity
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

# **Maximum Ratings**

- Operating Junction Temperature: -50°C to +150°C
- Storage Temperature: -50°C to +150°C


			1	
MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number	-	Peak	Voltage	Blocking
		Reverse	-	Voltage
		Voltage		Ū
MBR1020FCT	MBR1020FCT	20V	14V	20V
MBR1030FCT	MBR1030FCT	30V	21V	30V
MBR1040FCT	MBR1040FCT	40V	28V	40V
MBR1045FCT	MBR1045FCT	45V	31.5V	45V
MBR1050FCT	MBR1050FCT	50V	35V	50V
MBR1060FCT	MBR1060FCT	60V	42V	60V
MBR1080FCT	MBR1080FCT	80V	56V	80V
MBR10100FCT	MBR10100FCT	100V	70V	100V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	10 A	$T_{\rm C} = 100^{\circ}{\rm C}$
Peak Forward Surge Current	I <sub>FSM</sub>	120A	8.3ms, half sine
Maximum Instantaneous Forward Voltage 1020FCT-1045FCT 1050FCT-1060FCT 1080FCT-10100FCT	VF	.55V .75V .85V	$T_J = 25^{\circ}C$ $I_{FM} = 5A;$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	0.1mA 50mA	T <sub>c</sub> = 25°C T <sub>c</sub> = 100°C

# MBR1020FCT THRU MBR10100FCT

10 Amp Schottky Barrier Rectifier 20 to 100 Volts



		DIME	INSIONS		-
	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.583	.606	14.80	15.40	
В		.406		10.30	
С	.100	.112	2.55	2.85	
D	.248	.272	6.30	6.90	
Е		.161		4.10	
F		.071		1.80	
G	.512	.543	13.00	13.80	
Н	.100		2.55		
-		.035		0.90	
J		.032		0.80	
К	.118	.134	3.00	3.40	Ø
L		.189		4.80	
М		.130		3.30	
Ν	.098	.114	2.50	2.90	
0		.055		1.40	

www.mccsemi.com

## MBR1020FCT thru MBR10100FCT



**Micro Commercial Components** 





Fig. 1-FORWARD CURRENT DERATING CURVE



INSTANTANEOUS FORWARD CHARACTERISTIC

#### Fig. 2-TYPICAL INSTNATANEOUS FORWARD CHARACTERISTIC




Fig. 3-MAXIMUM NON-REPETITIVE SURGE CURRENT

www.mccsemi.com



**Micro Commercial Components** 

### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by Micro Commercial Components Corp. are not intended for use in Medical,

Aerospace or Military Applications.

# www.mccsemi.com