

Applications

- Evaporator sensor for air conditioning systems
- Heating systems

Features


- Copper case
- Twin cable (black)
- PVC-insulated wires with tinned ends,
 $T_{\max} = 105\text{ °C}$

Options

Alternative resistance ratings, rated temperatures, resistance tolerances, wire lengths and AWG 22, 24 or 26 available on request

Delivery mode

Bulk



Dimensions in mm

Climatic category (IEC 60068-1)		30/100/56	
Max. power at 25 °C	P_{25}	60	mW
Resistance tolerance	$\Delta R_N/R_N$	± 3 %	
Rated temperature	T_N	25	°C
B value tolerance	$\Delta B/B$	± 0,5 %	
Dissipation factor (in air)	δ_{th}	approx. 5	mW/K
Thermal cooling time constant (in air)	τ_c	approx. 50	s
Thermal time constant (in water)	τ_a	approx. 8	s
Heat capacity	C_{th}	approx. 250	mJ/K
Insulation resistance ($V = 100\text{ Vdc}$)	R_{is}	> 100	MΩ
Test voltage ($t = 1\text{ s}$)	V_T	1,5	kVAC

Type	AWG	R_{25} Ω	No. of R/T characteristic	$B_{25/100}$ K	Ordering code
K 500	26	10,0 k	8016	3988	B57500K0103A001
K 501	24	6,8 k	8016	3988	B57501K0682A002

Reliability data

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature $T: 100\text{ °C}$ $t: 1000\text{ h}$	< 2 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 56 days	< 2 %	No visible damage
Storage in coldness		Storage at lower category temperature $T: -30\text{ °C}$ $t: 1000\text{ h}$	< 2 %	No visible damage
Rapid temperature cycling (in fluid)	IEC 60068-2-14	Lower test temperature: 0 °C Upper test temperature: 100 °C Time to change from lower to upper temperature: < 30 s Number of cycles: 1000 Medium: oil	< 2 %	No visible damage
Vibration resistance	IEC 60068-2-6	Frequency range: 5 to 500 Hz Amplitude: 7,5 mm/2 g Duration: 3 × 8 h	< 3 %	No visible damage
Long-term stability (empirical value)		$T: 100\text{ °C}$ $t: 10\,000\text{ h}$	< 3 %	No visible damage
Voltage proof test		1500 Vac; 1 s		No flashover
Insulation test		The sensors are placed in a vessel containing metallic balls of 1 mm diameter (with total immersed head). The applied voltage is 100 Vdc.		Above 100 MΩ

Herausgegeben von EPCOS AG

Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.