

VCO Product Specification

 Model:
 VC0790-915K
 Rev:
 P1
 Date:
 9/14/2004

 Customer:
 SIRENZA MICRODEVICES

Operating Temperature Range: (-40 ° to 85 ° C)

		1	1	1	1	· · ·
Parameter	Min	Тур	Мах	Units	X	Remarks
Frequency Range -	800		1030	MHz	Х	
Tuning Voltage:						
800 MHz	0.4	0.9		Vdc	Х	
1030 MHz		3	3.5	Vdc	Х	
Tuning Sensitivity -	75	90	140	MHz/V	Х	
Output Power -	3	6	9	dBm	Х	
Output Phase Noise:						
10 kHz		-93	-82	dBc/Hz		
100 kHz		-113	-103	dBc/Hz	Х	
Power Supply -	3.9	4.1	4.3	Volts		
Supply Current -		25	32	mA	X	Vcc=4.1V
Harmonic Suppression:						
2nd Harmonic		-18	-10	dBc	X	
Spurious (Non-Harmonic) -			-50	dBc		
Frequency Pushing - 3.9 - 4.3V		1	10	MHz p-p		
Frequency Pulling -		15	34	MHz p-p		
Tuning Port Capacitance -		10		pF		

Package Information

Package Type:	к	Drawing Number:	60879
Dimensions:	0.3 x 0.3 x 0.079 inches	Drawing Revision:	с

Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.

Page 1 of 1

Sirenza Microdevices, Inc.

303 S. Technology Ct.

Broomfield, CO 80021

fax 303.410.7988

tel 303.327.3030

www.DataSheet4U.com