



Sensitive Gate Silicon Controlled - Rectifiers

Features

Repetitive Peak Off-State Voltage : 400V
 R.M.S On-State Current ($I_{T(RMS)} = 0.8 \text{ A}$)
 Low On-State Voltage (1.2V(Typ.)@ I_{TM})
 Available with tape & reel

Symbol 	$BV_{DRM} = 600\text{V}$ $I_{T(RMS)} = 0.8 \text{ A}$ $I_{TSM} = 10 \text{ A}$
SOT- 89 	

General Description

Sensitive-gate triggering thyristor is suitable for the application where gate current limited such as small motor control, gate driver for large thyristor, sensing and detecting circuits.

Absolute Maximum Ratings ($T_J = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Condition	Ratings	Units
V_{DRM}	Repetitive Peak Off-State Voltage	sine wave, 50 to 60Hz, gate open	400	V
$I_{T(AV)}$	Average On-State Current	half sine wave : $T_C = 112^\circ\text{C}$	0.5	A
$I_{T(RMS)}$	R.M.S On-State Current	180° Conduction Angle	0.8	A
I_{TSM}	Surge On-State Current	1/2 Cycle, 60Hz, sine wave non-repetitive, $t = 8.3\text{ms}$	10	A
I^2t	I^2t for Fusing	$t = 8.3\text{ms}$	0.415	A^2s
P_{GM}	Forward Peak Gate Power Dissipation	$T_A = 25^\circ\text{C}$, pulse width $1.0\mu\text{s}$	2	W
$P_{G(AV)}$	Forward Average Gate Power Dissipation	$T_A = 25^\circ\text{C}$, $t = 8.3\text{ms}$	0.1	W
I_{FGM}	Forward Peak Gate Current	$T_A = 25^\circ\text{C}$, pulse width $1.0\mu\text{s}$	1	A
V_{RGM}	Reverse Peak Gate Voltage	$T_A = 25^\circ\text{C}$, pulse width $1.0\mu\text{s}$	5.0	V
T_J	Operating Junction Temperature		-40 ~ 125	$^\circ\text{C}$
T_{STG}	Storage Temperature		-40 ~ 150	$^\circ\text{C}$







MCK100-6

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Items	Conditions	Ratings			Unit
			Min.	Typ.	Max.	
I_{DRM}	Repetitive Peak Off-State Current	$V_{AK} = V_{DRM}$ or V_{RRM} ; $R_{GK} = 1000$ $T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$			10 200	μA
V_{TM}	Peak On-State Voltage (1)	($I_{TM} = 1 \text{ A}$, Peak)		1.2	1.7	V
I_{GT}	Gate Trigger Current (2)	$V_{AK} = 6 \text{ V}$, $R_L = 100$ $T_C = 25^\circ\text{C}$ $T_C = -40^\circ\text{C}$			200 500	μA
V_{GT}	Gate Trigger Voltage (2)	$V_D = 7 \text{ V}$, $R_L = 100$ $T_C = 25^\circ\text{C}$ $T_C = -40^\circ\text{C}$			0.8 1.2	V
V_{GD}	Non-Trigger Gate Voltage (1)	$V_{AK} = 12 \text{ V}$, $R_L = 100$ $T_C = 125^\circ\text{C}$	0.2			V
dv/dt	Critical Rate of Rise Off-State Voltage	$V_D = \text{Rated } V_{DRM}$, Exponential waveform, $R_{GK} = 1000$ $T_J = 125^\circ\text{C}$	500	800		V/ μs
di/dt	Critical Rate of Rise On-State Current	$I_{PK} = 20 \text{ A}$; $P_W = 10 \mu\text{s}$; $di_G/dt = 1 \text{ A}/\mu\text{s}$ $I_{gt} = 20 \text{ mA}$			50	A/ μs
I_H	Holding Current	$V_{AK} = 12 \text{ V}$, Gate Open Initiating Current = 20mA $T_C = 25^\circ\text{C}$ $T_C = -40^\circ\text{C}$		2	5.0 10	mA
$R_{th(j-c)}$	Thermal Impedance	Junction to case			15	°C/W
$R_{th(j-a)}$	Thermal Impedance	Junction to Ambient			125	°C/W

Notes :

1. Pulse Width 1.0 ms , Duty cycle 1%
2. Does not include R_{GK} in measurement.

MCK100-6**Fig 1. Gate Characteristics****Fig 2. Maximum Case Temperature****Fig 3. Typical Forward Voltage****Fig 4. Thermal Response****Fig 5. Typical Gate Trigger Voltage vs. Junction Temperature****Fig 6. Typical Gate Trigger Current vs. Junction Temperature**

MCK100-6

Fig 7. Typical Holding Current





Fig 8. Power Dissipation



MCK100-6

SOT- 89 Package Dimension

Dim.	mm			Inch		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.40		1.60	0.055		0.063
B	0.36		0.56	0.014		0.022
B1	0.32		0.52	0.013		0.020
C	0.35		0.44	0.014		0.017
C1	0.35		0.44	0.014		0.017
D	4.40		4.60	0.173		0.181
D1	1.40		1.80	0.055		0.071
E	2.30		2.60	0.091		0.102
e		1.50			0.060	
e1	2.90		3.10	0.114		0.122
H	3.94		4.25	0.155		0.167
L	0.90		1.10	0.035		0.043
R		0.25			0.010	

