

KBPC10005P Thru KBPC1010P




10 AMP SILICON BRIDGE RECTIFIER

FEATURES


- Rating to 1000V PRV
- Ideal for printed circuit board
- Surge overload rating to 150 Amperes peak
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- UL recognized: File #E106441
- UL recognized 94V-O plastic material

Mechanical Data

- Case: Molded Plastic
- Leads: Silver plated copper
- Leads solderable per MIL-STD-202, Method 208
- Mounting: Through hole for #6 screw
- Weight: 0.18 ounce, 5.4 grams



Outline Drawing



Maximum Ratings & Characteristics

- Ratings at 25° C ambient temperature unless otherwise specified
- Single phase, half wave, 60Hz, resistive or inductive load
- For capacitive load, derate current by 20%

		KBPC 10005P	KBPC 1001P	KBPC 1002P	KBPC 1004P	KBPC 1006P	KBPC 1008P	KBPC 1010P	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Output Current	$I_{(AV)}$				10.0 8.0				A
Peak Forward Surge Current 8.3 ms Single Half-Sine-Wave Superimposed On Rated Load	I_{FSM}				150				A
Maximum DC Forward Voltage Drop per Element At 5.0A DC	V_F				1.1				V
Maximum Reverse Current At Rated DC Blocking Voltage per Element	I_R				10 1				μA mA
$I^2 t$ Rating for Fusing ($t < 8.3ms$)	$I^2 t$				64				A ² S
Typical Thermal Resistance	R_{THJC}				5				°C/W
Operating Temperature Range	T_J				-55 to +125				°C
Storage Temperature Range	T_{STG}				-55 to +150				°C

Note: * Unit mounted on metal chassis.
** Unit mounted on P.C. board.