

VCO Product Specification

Model: VCO-103TC **Rev:** - **Date:** 7/22/2002

Customer: VARI-L COMPANY

Operating Temperature Range: (-55 ° to 100 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	50		100	MHz	X	
Tuning Voltage:						
50 MHz	0	1.4		Vdc	X	
100 MHz		16.4	20	Vdc	X	
Tuning Sensitivity:						
50 MHz	1.8	2.4	3	MHz/V	X	
62.5 MHz	2.7	3.6	4.5	MHz/V	X	
75 MHz	2.9	3.8	4.8	MHz/V	X	
87.5 MHz	2.8	3.7	4.7	MHz/V	X	
100 MHz	1.6	2.1	2.7	MHz/V	X	
Output Power -	10	13	16	dBm	X	
Output Phase Noise:						
10 kHz		-108	-102	dBc/Hz	X	
100 kHz		-128	-122	dBc/Hz	X	
1000 kHz		-148	-142	dBc/Hz	X	
Power Supply -	14.75	15	15.25	Volts	X	
Supply Current -		12.5	15	mA	X	
Harmonic Suppression:						
2nd Harmonic		-12	-10	dBc	X	
3rd Harmonic		-12	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.75-15.25		0.05	0.2	MHz p-p		
Frequency Pulling - 12 dB RL		1	3	MHz p-p		
Output Impedance -		50		Ω		
Modulation:						
Bandwidth	100	175		kHz		
Input Impedance		0.05		kΩ		

Package Information

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	P

Comments

X Indicates parameter to be tested 100% in production

4895 Peoria Street Denver, CO 80239 tel: 303.371.1560 fax: 303.371.0845 sales@vari-l.com	Our Products Include:	PLL Synthesizer Modules	Narrow-Band Voltage Controlled Oscillators	ISO 9001 Certified
		Wide-Band Voltage Controlled Oscillators	Couplers	
Contact the Vari-L Sales Department for custom solutions to your RF and microwave component assembly needs.				
Vari-L Company, Inc. www.vari-l.com				