



## VCO Product Specification

**Model:** VCO-104TC      **Rev:** -      **Date:** 7/31/2002

**Customer:** VARI-L COMPANY

**Operating Temperature Range:** ( -55 ° to 100 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	100		200	MHz	X	
Tuning Voltage:						
100 MHz	0	1.4		Vdc	X	
200 MHz		16.8	20	Vdc	X	
Tuning Sensitivity:						
100 MHz	4.8	6.4	8	MHz/V	X	
125 MHz	5.3	7.1	8.9	MHz/V	X	
150 MHz	5.6	7.5	9.4	MHz/V	X	
175 MHz	5.7	7.6	9.5	MHz/V	X	
200 MHz	2.4	3.2	4.4	MHz/V	X	
Output Power -	10	12.5	16	dBm	X	
Output Phase Noise:						
10 kHz		-99	-93	dBc/Hz	X	
100 kHz		-122	-116	dBc/Hz	X	
1000 kHz		-144	-138	dBc/Hz	X	
Power Supply -	14.75	15	15.25	Volts	X	
Supply Current -		12.5	15	mA	X	
Harmonic Suppression:						
2nd Harmonic		-12	-10	dBc	X	
3rd Harmonic		-12	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.75-15.25 V		0.3	1	MHz p-p		
Frequency Pulling - 12 dB RI		3	6	MHz p-p		
Output Impedance -		50		Ω		
Modulation:						
Bandwidth	250	350		kHz		
Input Impedance		0.05		kΩ		

### Package Information

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	P

### Comments

X Indicates parameter to be tested 100% in production

Page 1 of 1

4895 Peoria Street Denver, CO 80239 tel: 303.371.1560 fax: 303.371.0845 sales@vari-l.com	<b>Our Products Include:</b>	PLL Synthesizer Modules	Narrow-Band Voltage Controlled Oscillators	<b>ISO 9001 Certified</b>
		Wide-Band Voltage Controlled Oscillators	Couplers	
Contact the Vari-L Sales Department for custom solutions to your RF and microwave component assembly needs.				
<b>Vari-L Company, Inc.    www.vari-l.com</b>				