



## VCO Product Specification

**Model:** VCO-106      **Rev:** A      **Date:** 7/22/2002

**Customer:** VARI-L COMPANY

**Operating Temperature Range:** ( -55 ° to 100 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	400		800	MHz	X	
Tuning Voltage:						
400 MHz	0	1.3		Vdc	X	
800 MHz		18	20	Vdc	X	
Tuning Sensitivity:						
400 MHz	19.5	26	32.5	MHz/V	X	LINEARITY Less Than 4:1
500 MHz	23.2	31	38.8	MHz/V	X	
600 MHz	29.2	39	48.8	MHz/V	X	
700 MHz	18	24	30	MHz/V	X	
800 MHz	8.2	11	13.8	MHz/V	X	
Output Power -	10	12	16	dBm	X	
Output Phase Noise:						
10 kHz		-95	-89	dBc/Hz	X	
100 kHz		-120	-114	dBc/Hz	X	
1000 kHz		-143	-137	dBc/Hz	X	
Power Supply -	14.75	15	15.25	Volts	X	
Supply Current -		16	18	mA	X	
Harmonic Suppression:						
2nd Harmonic		-13	-10	dBc	X	
3rd Harmonic		-13	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.75-15.25 V		0.5	1	MHz p-p		
Frequency Pulling - 12 dB RL		22	28	MHz p-p		
Output Impedance -		50		Ω		
Modulation:						
Bandwidth	10000	15000		kHz		
Input Impedance		0.05		kΩ		

### Package Information

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	P

### Comments

X Indicates parameter to be tested 100% in production

Page 1 of 1

4895 Peoria Street Denver, CO 80239 tel: 303.371.1560 fax: 303.371.0845 sales @ vari-l.com	Our Products Include:	PLL Synthesizer Modules	Narrow-Band Voltage Controlled Oscillators	ISO 9001 Certified
		Wide-Band Voltage Controlled Oscillators	Couplers	
Contact the Vari-L Sales Department for custom solutions to your RF and microwave component assembly needs.				
<b>Vari-L Company, Inc.    www.vari-l.com</b>				