



## VCO Product Specification

**Model:** VCO-107TC      **Rev:** B      **Date:** 7/23/2002

**Customer:** VARI-L COMPANY

**Operating Temperature Range:** ( -55 ° to 100 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	500		1000	MHz	X	
Tuning Voltage:						
500 MHz	1	1.8		Vdc	X	
1000 MHz		17.1	20	Vdc	X	
Tuning Sensitivity:						
500 MHz	24	31.3	39	MHz/V	X	
625 MHz	23	30.6	38	MHz/V	X	
750 MHz	34	45.6	57	MHz/V	X	
875 MHz	28	37.2	47	MHz/V	X	
1000 MHz	13	17.8	22	MHz/V	X	
Output Power -	10	13.5	16	dBm	X	
Output Phase Noise:						
10 kHz		-92	-86	dBc/Hz	X	
100 kHz		-117	-111	dBc/Hz	X	
1000 kHz		-140	-134	dBc/Hz	X	
Power Supply -	14.75	15	15.25	Volts	X	
Supply Current -		15.4	18	mA	X	
Harmonic Suppression:						
2nd Harmonic		-13	-10	dBc	X	
3rd Harmonic		-13	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.75-15.25V		10	14	MHz p-p		
Frequency Pulling - 20 dB RL		12	20	MHz p-p		
Output Impedance -		50		Ω		
Modulation:						
Bandwidth	15000	20000		kHz		
Input Impedance		0.05		kΩ		

### Package Information

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	P

### Comments

**X** Indicates parameter to be tested 100% in production

Page 1 of 1

4895 Peoria Street Denver, CO 80239 tel: 303.371.1560 fax: 303.371.0845 sales@vari-l.com	<b>Our Products Include:</b>	PLL Synthesizer Modules	Narrow-Band Voltage Controlled Oscillators	<b>ISO 9001 Certified</b>
		Wide-Band Voltage Controlled Oscillators	Couplers	
Contact the Vari-L Sales Department for custom solutions to your RF and microwave component assembly needs.				
<b>Vari-L Company, Inc.    www.vari-l.com</b>				