



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

1N34A Point Contact Germanium Diode

Description:

The 1N34A is a point contact diode in a DO7 type package employing N-form Germanium and gives an efficient and excellent linearity when used in TV image detection, FM detection, radio AM detection, etc.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Peak Reverse Voltage, V_{RM}	45V
Reverse Voltage DC, V_R	20V
Peak Forward Current, I_{FM}	150mA
Average Rectified Output Current, I_O	50mA
Surge Forward Current, I_{surge}	500mA
Operating Junction Temperature, T_J	+75°C
Storage Temperature Range, T_{stg}	-55° to +75°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Current	I_F	$V_F = 1\text{V}$	4	-	-	mA
Reverse Current	I_R	$V_R = 10\text{V}$	-	-	50	μA
Junction Capacitance	C_j	$F = 1\text{Mhz}, V = -1\text{V}$	-	-	1	pF
Rectification Efficiency	η	$V_i = 2V_{rms}, = 5K\Omega, C = 20\text{pF}, f = 40\text{MHz}$	55	-	-	%

