



SUPER FAST GLASS PASSIVATED RECTIFIER

SF11G/RG THRU SF18G/RG


VOLTAGE RANGE **50 to 1000 Volts**
CURRENT **1.0 Ampere**

FEATURES

- Super fast switching speed
- Glass passivated chip junction
- Low power loss, high efficiency
- Low leakage
- High surge capacity
- High temperature soldering guaranteed
260°C/10 second, 0.375" (9.5mm) lead length
- SF11G Packing DO-41, SF11RG Packing R-1.

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Polarity: Color Band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.33 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	SF 11G/RG	SF 12G/RG	SF 13G/RG	SF 14G/RG	SF 15G/RG	SF 16G/RG	SF 17G/RG	SF 18G/RG	UNIT	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	150	200	300	400	500	600	Volts	
Maximum RMS Voltage	V_{RMS}	35	70	105	140	210	280	350	420	Volts	
Maximum DC Blocking Voltage	V_{DC}	50	100	100	200	300	400	500	600	Volts	
Maximum Average Forward Rectified Current 0.375" (9.5mm) lead length at $T_A=55^\circ\text{C}$	$I_{(AV)}$	1.0								Amps	
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	30								Amps	
Maximum Instantaneous Forward Voltage at 1.0A	V_F	0.95			1.25		1.7			Volts	
Maximum DC Reverse Current at rated DC Blocking Voltage at	I_R	$T_A = 25^\circ\text{C}$								5.0	μA
		$T_A = 125^\circ\text{C}$									
Maximum Reverse Recovery Time Test conditions $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$	t_{rr}	35								nS	
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	C_j	15			10					pF	
Typical Thermal Resistance (NOTE 1)	$R_{\theta JC}$	60								°C/W	
Operating Junction Temperature Range	T_j	(-55 to +150)								°C	
Storage Temperature Range	T_{STG}	(-55 to +150)								°C	

Notes:

1. Thermal resistance from junction to ambient with 0.375" (9.5mm) lead length, PCB mounted.



SUPER FAST GLASS PASSIVATED RECTIFIER

SF11G/RG THRU SF18G/RG

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 1.0 Ampere

RATING AND CHARACTERISTIC CURVES SF11G/RG THRU SF18G/RG

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES : 1. Rise Time=7ns max. Input Impedance= 1 magohm, 22pF
2. Rise time=10ns max. Source Impedance= 50 ohms

SET TIME BASE f 50/100ns/cm