


## Ultra Fast Avalanche Sinterglass Diode

### Features

- Glass passivated
- Hermetically sealed axial leaded glass envelope
- Low reverse current
- High reverse voltage

### Applications

Switched mode power supplies  
High-frequency inverter circuits



949588

### Mechanical Data

**Case:** Sintered glass case, SOD 64

**Terminals:** Plated axial leads, solderable per MIL-STD-750, Method 2026

**Polarity:** Color band denotes cathode end

**Mounting Position:** Any

**Weight:** 860 mg, (max. 1000 mg)

### Parts Table

Part	Type differentiation	Package
SF5400	$V_R = 50 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5401	$V_R = 100 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5402	$V_R = 200 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5403	$V_R = 300 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5404	$V_R = 400 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5405	$V_R = 500 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5406	$V_R = 600 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5407	$V_R = 800 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64
SF5408	$V_R = 1000 \text{ V}; I_{FAV} = 3 \text{ A}$	SOD64

### Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

Parameter	Test condition	Sub type	Symbol	Value	Unit
Reverse voltage = Repetitive peak reverse voltage	see electrical characteristics	SF5400	$V_R = V_{RRM}$	50	V
	see electrical characteristics	SF5401	$V_R = V_{RRM}$	100	V
	see electrical characteristics	SF5402	$V_R = V_{RRM}$	200	V
	see electrical characteristics	SF5403	$V_R = V_{RRM}$	300	V
	see electrical characteristics	SF5404	$V_R = V_{RRM}$	400	V
	see electrical characteristics	SF5405	$V_R = V_{RRM}$	500	V
	see electrical characteristics	SF5406	$V_R = V_{RRM}$	600	V
	see electrical characteristics	SF5407	$V_R = V_{RRM}$	800	V
	see electrical characteristics	SF5408	$V_R = V_{RRM}$	1000	V
Peak forward surge current	$t_p = 10\text{ ms}$ , half sinewave		$I_{FSM}$	150	A
Average forward current			$I_{FAV}$	3	A
Junction and storage temperature range			$T_j = T_{stg}$	- 55 to + 175	$^{\circ}\text{C}$
Non repetitive reverse avalanche energy	$I_{(BR)R} = 0.4\text{ A}$		$E_R$	10	mJ

### Maximum Thermal Resistance

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

Parameter	Test condition	Sub type	Symbol	Value	Unit
Junction ambient	Lead length $l = 10\text{ mm}$ , $T_L = \text{constant}$		$R_{thJA}$	25	K/W
	on PC Board with spacing 25 mm		$R_{thJA}$	70	K/W

### Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

Parameter	Test condition	Sub type	Symbol	Min	Typ.	Max	Unit
Forward voltage	$I_F = 3\text{ A}$	SF5400- SF5404	$V_F$			1.1	V
	$I_F = 3\text{ A}$	SF5405- SF5408	$V_F$			1.7	V
Reverse current	$V_R = V_{RRM}$		$I_R$			5	$\mu\text{A}$
	$V_R = V_{RRM}$ , $T_j = 125\text{ }^{\circ}\text{C}$		$I_R$			50	$\mu\text{A}$

Parameter	Test condition	Sub type	Symbol	Min	Typ.	Max	Unit
Reverse breakdown voltage	$I_R = 100 \mu A$	SF5400	$V_{(BR)R}$	60			V
	$I_R = 100 \mu A$	SF5401	$V_{(BR)R}$	110			V
	$I_R = 100 \mu A$	SF5402	$V_{(BR)R}$	220			V
	$I_R = 100 \mu A$	SF5403	$V_{(BR)R}$	330			V
	$I_R = 100 \mu A$	SF5404	$V_{(BR)R}$	440			V
	$I_R = 100 \mu A$	SF5405	$V_{(BR)R}$	550			V
	$I_R = 100 \mu A$	SF5406	$V_{(BR)R}$	660			V
	$I_R = 100 \mu A$	SF5407	$V_{(BR)R}$	880			V
	$I_R = 100 \mu A$	SF5408	$V_{(BR)R}$	1100			V
Reverse recovery time	$I_F = 0.5 A, I_R = 1 A, i_R = 0.25 A$	SF5400-SF5404	$t_{rr}$			50	ns
	$I_F = 0.5 A, I_R = 1 A, i_R = 0.25 A$	SF5405-SF5408	$t_{rr}$			75	ns

### Typical Characteristics ( $T_{amb} = 25^\circ C$ unless otherwise specified)




Figure 1. Max. Thermal Resistance vs. Lead Length




Figure 3. Max. Average Forward Current vs. Ambient Temperature




Figure 2. Max. Average Forward Current vs. Ambient Temperature




Figure 4. Max. Average Forward Current vs. Ambient Temperature




Figure 5. Max. Average Forward Current vs. Ambient Temperature




Figure 8. Max. Reverse Current vs. Junction Temperature




Figure 6. Max. Forward Current vs. Forward Voltage




Figure 9. Max. Reverse Power Dissipation vs. Junction Temperature




Figure 7. Max. Forward Current vs. Forward Voltage





Figure 10. Diode Capacitance vs. Reverse Voltage

## Package Dimensions in mm



### Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**Vishay Semiconductor GmbH** has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**Vishay Semiconductor GmbH** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design  
and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423