



- Resistances from 0.10Ohm to 500MOhms
- Power Rating 0.1 to 0.25Watt
- Resistance Tolerances to $\pm 0.5\%$
- TCR's to ± 50 ppm/K
- Thick Film Resistance Element
- Sizes: 0504 / 0603 / 0805 / 1206

SPECIFICATIONS


Type		0504	0603	0805	1206
Power Rating (W) ¹		0.10	0.10	0.125	0.25
Working Voltage (VAC)	Trimmed	50	75	100	200
	Untrimmed	150	220	300	600
Resistance Range (Ω)	Tolerances Available (%) Temperature Coefficients Available (\pm ppm/K) ² (lower TCR upon request)				
0.1 Ω - <1 Ω		-	10% to 20% 250	5% to 20% 250	5% to 20% 250
1 Ω - <10 Ω		5% to 20% 100 / 250	5% to 20% 100 / 250	2% to 20% 100 / 250	2% to 20% 100 / 250
10 Ω - <100 Ω		2% to 10% 100	1% to 10% 100	1% to 10% 50 / 100	1% to 10% 50 / 100
100 Ω - 1M		1% to 10% 50 / 100	1% to 10% 50 / 100	0.5% to 10% 50 / 100	0.5% to 10% 50 / 100
>1M - 10M		1% to 10% 50 / 100	1% to 10% 50 / 100	0.5% to 10% 50 / 100	0.5% to 10% 50 / 100
>10M - 100M		2% to 20% 100 / 250	1% to 20% 50 / 100	0.5% to 20% 50 / 100	0.5% to 20% 50 / 100
>100M - 500M		-	5% to 20% 100 / 250	2% to 20% 100 / 250	2% to 20% 100 / 250

¹W @ 70 °C / 0W @ 155 °C
²50 PPM : +25 °C to +125 °C

Specification	Value
Temperature Range	-55°C to +155°C
Climactic Category	55 / 155 / 56
Solderability	250°C / 3s
Max. Soldering Temperature	260°C / 10s

SPECIFICATIONS (continued)

Long Term Stability	Max ΔR		
	<10 Ω	10 Ω - 100M	>100M
Storage 125°C / 1000h	±1%	±0.5%	±1%
Storage 155°C / 1000h	±2%	±1%	±2%
Load Life / P=70% / 70°C / 1000h	±1%	±0.5%	±1%
Short term overload	±0.5%	±0.25%	±0.5%
Humidity / 96%RH / 40°C / 56 days	±1%	±0.5%	±1%




Type (larger sizes upon request)	Dimensions			
	L	B	D	C
CRS 0504	0.050 +0.006 / -0.002 [1.25 +0.15 / -0.05]	0.040 +0.006 / -0.002 [1.0 +0.15 / -0.05]	0.012 +0.006 / -0.002 [0.3 +0.15 / -0.05]	0.008 +0.008 / -0.004 [0.2 +0.2 / -0.1]
CRS 0603	0.060 +0.006 / -0.002 [1.5 +0.15 / -0.05]	0.030 +0.006 / -0.002 [0.8 +0.15 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.008 +0.008 / -0.004 [0.2 +0.2 / -0.1]
CRS 0805	0.080 +0.006 / -0.002 [2.0 +0.15 / -0.05]	0.050 +0.006 / -0.002 [1.25 +0.15 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.012 +0.008 / -0.004 [0.3 +0.2 / -0.1]
CRS 1206	0.126 +0.006 / -0.002 [3.2 +0.15 / -0.05]	0.060 +0.008 / -0.002 [1.5 +0.2 / -0.05]	0.016 +0.006 / -0.002 [0.4 +0.15 / -0.05]	0.012 +0.008 / -0.004 [0.3 +0.2 / -0.1]

Packaging:

Bulk or Blister tape to IEC 60286-3

- Tape width 8mm / Reel Diameter 180 or 330mm
- Minimum quantity Bulk / 100 pieces per value
- Minimum quantity Tape & Reel / 1000 pieces per value

Power Derating Curve



Ordering Information

Part Number - Resistance - Tolerance - TCR - Packaging

Example: CRS 0603 1 Ohm 5% 100ppm Tape

(Note: if no TCR is specified, the highest value will be supplied)