

tyco / *Electronics*

M/A-COM

M/A-COM
RF & Microwave Products


E-Series 75 Ohm Coupler 5 - 1000 MHz

Features

- Coupling 13db Typical
- Surface Mount
- Tape and Reel Packaging available



SM-22 Package



Description

M/A-COM's EMDC-13-1-75 is a high performance 75 Ohm Coupler, in an SM-22, surface mount package. The EMDC-13-1-75 is designed for use in high volume CATV applications. Typical applications include Set-top Boxes, Network Interface Units, Cable Amplifiers and Headend equipment.

Electrical Specifications @25°C

Frequency Range 5 - 1000 MHz	Units	Nominal	Typical	Minimum	Maximum
Mainline Loss					
5 - 50 MHz	dB	—	1.5	—	2.2
50 - 500 MHz	dB	—	1.3	—	2.0
500 - 1000 MHz	dB	—	1.3	—	2.0
Coupling					
5 - 1000 MHz	dB	13 ± 1.1	—	—	—
Coupling Flatness	dB	—	—	—	0.9
Directivity					
5 - 50 MHz	dB	—	25	20	—
50 - 500 MHz	dB	—	20	15	—
500 - 1000 MHz	dB	—	13	7	—
Return Loss, all Ports					
5 - 1000 MHz	dB	—	14	8	—

Please Note that the photograph above indicates package shape only, unit may be wired differently.

S 1360 D

M/A-COM
RF & Microwave Products

M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks.
Specifications subject to change without notice.

Connecting
at a
HIGHER
level.™
AMP

Absolute Maximum Ratings


Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Operating/Storage Temperature	-20°C to +85°C

Operating Characteristics


Function	Pin No.
Input	3
Output	4
Coupled	1
Ground	2
Case Ground	—
External 75 Ohms	5
Not Connected	—

Typical Performance @ 25°C


Mainline Loss




Directivity




Coupling




Input Return Loss



Output Return Loss



Coupling Return Loss



S 1360 D



M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

www.macom.com

AMP and Connecting at a Higher Level are trademarks. Specifications subject to change without notice.

